91

D15-199


3/Emil.



nylomatic














standard parts catalog

precision plastic mechanical / electronic components for industry

nylomatic division nolan avenue morrisville, bucks co., pennsylvania 19067

6/69



NYLOMATIC MANUFACTURERS OF PLASTIC MECHANICAL PARTS

NOLAN AVENUE, MORRISVILLE, PENNSYLVANIA 19067/TELEPHONE (215) 295-4151

THANK YOU FOR YOUR INQUIRY.....

Your interest in Nylomatic products and services is appreciated.

We are pleased to send you the attached information. We'll be even more pleased to earn the privilege of counting you as a valued Nylomatic customer for one or more of our 3000 stock items...and our complete custom molding, stamping and machining services.

If we may be of further help with product data or samples, please call us at our home office (area code 215) 295-4151 or contact our local representative in your area:

California, Nevada & Arizona

Littrell Western Sales, Inc. 3121 East 12th St. Los Angeles, Calif. 94124 (213) 261-0164

100 Produce Ave., Suite 208 So. San Francisco, Calif. 94080 (415) 583-5572

Ohio, Western Penna., Indiana, Kentucky & Michigan

Luebbe Sales Co.

2649 Erie Ave. Cincinnati, O. 45208 (513) 871-4211

3490 S. Dixie Drive Dayton, O. 45439 (513) 294-0426 20905 Greenfield Rd. Southfield, Mich. 48075 (313) 357-0355

21330 Center Ridge Rd. Room 25A Cleveland, O. 44116 (216) 734-4242

Illinois, Wisconsin

Ralph T. Rose & Associates 334 Sutton Road Barrington, Ill. 60010 (312) 446-5950

New York City, Northern New Jersey & Florida


H. R. Williams Assocs., Inc. P. O. Box 344 Ridgewood, N. J. 07451 (201) 444-5392

New England

Staley Associates
P. O. Box 205
Wellesley Hills, Mass. 02181
(617) 235-1643

leligie

A DIVISION OF WEHCO PLASTICS INC.



NYLOMATIC MANUFACTURERS OF PLASTIC MECHANICAL PARTS

NOLAN AVENUE, MORRISVILLE, PENNSYLVANIA 19067/TELEPHONE (215) 295-4151

THANK YOU FOR YOUR INQUIRY.....

Your interest in Nylomatic products and services is appreciated.


We are pleased to send you the attached information. We'll be even more pleased to earn the privilege of counting you as a valued Nylomatic customer for one or more of our 3000 stock items...and our complete custom molding, stamping and machining services.

If we may be of further help with product data or samples, please call us at our home office (area code 215) 295-4151 or contact our local representative in your area:



NYLON GEAR RACKS

the one source for plastic mechanical parts



14½° Pressure Angle

16 Pitch

24 Pitch

32 Pitch

48 Pitch

12" Lengths Easy To Cut or Extend
Dimensions and Prices on Next Page

Smooth & Quiet Operation

Low Inertia

Superior Wear Resistance


Corrosion Resistant

ie go

Call or Write


nylomatic division, nolan avenue, morrisville, pennsylvania 19067

telephone (215) 295-4151



nylomatic GEAR RACKS

- A \$25.00 set-up charge applies to each part ordered.
- Standard material is DuPont #101 nylon.
- Apply for prices on quantities larger than 5M pieces.
- Prices subject to change without notice.



	14½° PRESSURE ANGLE												
PART NO.	PITCH	CIRCULAR PITCH	TEETH	'A'	FACE	DEPTH	PRICE PLUS SETUP						
N1247-1*	16	.1963	62	.250"	5/16"	5/16"	\$264. M						
N1247-2	24	.1309	92	.208	1/4	1/4	195. M						
N1247-3	32	.0982	123	.156	3/16	3/16	153. M						
N1247-4	48	.0654	184	.104	1/8	1/8	120. M						

ENGINEERING KIT (4 EACH OF ABOVE 4 SIZES) AVAILABLE FOR \$14.00

16 pitch racks are recessed 3/32'' deep on both sides, allowing a 1/8''-wide rib down the center of rack. Cross ribs at 2'' intervals will permit easy drilling and fastening.

Note: 12" length is a nominal size. Racks are molded in proper lengths to permit end to end butting without interruption of tooth spacing. Unlimited, continuous lengths of rack are thus possible.

Call or Write

nylomatic division, nolan avenue, morrisville, pennsylvania 19067 telephone (215) 295-4151

nylomatic

CATALOG 55 SUPPLEMENT



16 PITCH SPUR GEARS (Pg. 5)												
PART	P.A.	TEETH	P.D.	HOLE	FACE	STYLE	Н	UB	PRICE			
NO.					17.02	OTT L	DIA.	PROJ.	PLUS SET-UP			
N6693	20°	30	1.875	.254	.379	Н	.990	5/16	\$230.00 M			
N6817	20°	30	1.875	.257 °D'	.379	Н	.990	1/8	\$230.00 M			

	24 PITCH SPUR GEARS (Pg. 6)												
PART	NO P.A. IEEIN P.D. HOLE FACE SIYLE PLUS SET UP												
NO.	NO. P.A. TEETH P.D. HOLE FACE STYLE DIA. PROJ. PLUS SET-UP												
N6724	20°	21	.875	.125	.250	Н	.500	.310	\$ 48.50 M				
N5827	20°	28	1.167	.370	.063	Н	7/16	.250	58.10 M				
N6856													
N1152A	20°	48	2.000	.218(†)	.250	Н	.647	.260	119.60 M				

 $(†) \pm .003$

Issued 6-69

							-		
			32 PIT	CH SPUR	GEARS (F	Pg. 7-8)			
PART NO.	P.A.	TEETH	P.D.	HOLE	FACE	STYLE	HL		PRICE PLUS SET-UP
							DIA.	PROJ.	
N6692	141/20	14	.438	.187	3/16	NH	-	-	\$ 34.66 M
N5521	141/20	18	.563	.283	.071	ЙН	-1		33.10 M
N5554	141/20	20	.625	.314	11/32	Н	.525	5/32	52.15 M
N6978	141/20	20	.625	.315	.218	Н	.500	.250	50.45 M
ND11	141/20	28	.875	.375	.187	NH	_	_	50.80 M
N6298A	141/20	32	1.000	.245	5/16	Н	5/8	1/4	85.80 M
N6874	141/20	32	1.000	.441	.440	Н	.687	.250	101.10 M
N6960	141/20	44	1.375	.315	.187	Н	5/8	.047	76.40 M
N7003	141/20	52	1.625	.441	.500	Н	.880	.380	159.60 M
N5444	141/20	62	1.938	.252	.125	Н	.614	.490	133.55 M
N6557	20°	19	.594	.251	.160	Н	.734	.094	49.05 M
N6825A	20°	24	.750	.130	.125	Н	.19	.025	43.20 M
N6877	20°	44	1.375	.378	3/16	Н	1-1/16	5/16	136.95 M
N6875	20°	44	1.375	.579	3/16	Н	1-1/16	5/16	136.95 M
N1189	20°	59	1.844	.621	.239	NH	-	-	132.30 M
N6876	20°	62	1.938	.253	3/16	Н	3/4	5/16	137.10 M
N1220	20°	72	2.250	.379K	3/16	Н	11/16	5/16	150.80 M
N1219	20°	80	2.500	.882	1/8	Н	1-1/16	.371	150.65 M

nylomatic division, nolan avenue, morrisville, pennsylvania, 19067 - telephone (215) 295-4151

CATALOG 55 SUPPLEMENT



			48 PIT	CH SPUR	GEARS (I	Pg. 9-10)			
PART.	P. A.	TEETH	P.D.	HOLE	FACE	STYLE	HU	В	PRICE
NO.		,,		11022		0.122	DIA.	PROJ.	PLUS SET-UP
N6642	141/20	12	.250	.125	1/8	NH			\$ 44.60 M
N6819	141/20	20	.417	.189	.187	Н	11/32	.125	47.20 M
N6848	141/20	24	.500	.256	.280	Н	.406	.03	49.40 M
N6820	141/20	32	.667	.189	.125	Н	1/2	1/4	50.50 M
N6641	141/20	36	.750	.250	1/8	NH	-	-	47.70 M
N6496	141/20	37	.771	.125	.215	NH		_	57.25 M
N6565	141/20	40	.833	.247'D'	.125	Н	.62	.250	53.10 M
*ND10	141/20	40	.833	.375	.312	Н	9/16	.250	53.10 M
N2145	141/20	42	.875	.250	.125	Н	.44	.250	53.85 M
N6576	141/20	44	.917	.125	.124	Н	.28	.131	53.95 M
N2127	20°	30	.625	.128	.055	Н	.25	.148	53.95 M
N6560	20°	36	.750	.246	.385	NH			47.70 M
N6559	20°	36	.750	.496	.450	Н	11/16	.100	49.85 M
N5691	20°	42	.875	.250	.125	Н	.437	.065	52.35 M

^{*}also has a 9/16 d. x .063 L. hub on other side


			М	ISC. SPU	R GEARS	(Pg. 1	1)					
PART	PITCH	P.A.	TEETH	P.D.	HOLE	FACE	STYLE	HL		PRICE PLUS SET-UP		
NO.								DIA.	PROJ.	FL03 3L1-01		
N6910	12	141/20	16	1.333	.378	.200	NH	_	-	\$ 67.60 M		
N1183	12	141/20	24	2.000	.673	1/4	NH	-	-	120.65 M		
N1183A	12	141/20	24	2.000	.880'DD'	1/4	NH	_	_	120.65 M		
N6992	20	20°	18	.900	.491	5/16	NH	_	_	63.80 M		
N6995	20	20°	22	1.100	.367	5/16	NH	_	_	64.90 M		
N1029A	20	20°	25	1.250	.314	3/16	Н	7/16	3/16	87.50 M		
N7002	64	20°	16	.250	.092	.125	NH	_		43.40 M		
N6943	64	141/20	96	1.500	.258	1/4	Н	5/8	1/4	69.00 M		

	COMBINATION GEARS (Pg. 12-14)													
PART			PINION					GEAF	2		HOLE	PRICE		
NO.	PITCH	P.A.	TEETH	P.D.	FACE	PITCH	P.A.	TEETH	P.D.	FACE	The services	PLUS SET-UP		
N5999	24	141/20	12	.500	.218	32	141/20	36	1.125	.124	.253	\$58.80 M		
*N6824	32 20° 10 .312 .196					32	32 20° 38 1.188 .114					47.90 M		
N6570	32	20°	10	.313	.343	48	20°	74	1.542	.188	.166	61.75 M		
N2104	110070							28	.875	.125	.187	57.80 M		
N5370	48	141/20	10	.208	.156	48	141/20	40	.833	.094	.096	50.00 M		
N6961	N6961 64 20° 40 .625 .46							40	1.250	.187	.252	84.35 M		

^{*}Available with either a .025 hub or a .350 x .06 counterbore nylomatic division, nolan avenue, morrisville, pennsylvania, 19067 - telephone(215) 295-4151

nylomatic

CATALOG 55 SUPPLEMENT



1/5" PITCH TIMING BELT PULLEYS (Pg. 17)*												
PART NO.	Grooves	P.D.	FACE	FLANGE O.D.	HOLE	KEYWAY	STYLE	DIA.	JB PROJ.	PRICE PLUS SET-UP		
	10	/27	9/32		19/64							
N6712 N5490-10	10	.637	.31	23/32	.250		H	23/32	9/32	\$150.00 M		
N6449	11					=	Н	9/16	1/4	150.00 M		
		.700	.54	.93	.250	- 001	NH	-		160.00 M		
N6452	11	.700	.54	.92	.312	.094 x .045	Н	1/2	5/32	160.00 M		
N6852	12	.764	.27	.80	.190	-	NH	_	_	170.00 M		
N5490-12	12	.764	.31	.92	.250	_	Н	9/16	1/4	170.00 M		
N5489-12	12	.764	.43	.92	.312	\\\	Н	9/16	1/4	170.00 M		
N6483	12	.764	.54	.98	.250	.062 x .030	NH	-	-	170.00 M		
N6448	12	.764	.54	.98	.312	$.094 \times .045$	Н	1/2	5/32	170.00 M		
N6497	12	.764	.54	.94	.375	.094 x .045	NH	- 1	-	170.00 M		
N6451	13	.828	.54	1.04	.400	$.094 \times .045$	NH	-	-	180.00 M		
N6962	14	.891	9/32	11/4	.315		Н	1.013	.258	190.00 M		
N5490-14	14	.891	.43	1.11	.250	-	Н	9/16	1/4	190.00 M		
N6455	14	.891	.54	1.11	.250	.062 x .040	NH	_	I [190.00 M		
N5973	15	.955	5/16	1.04	.255	<u> </u>	Н	5/8	1/8	200.00 M		
N6460	15	.955	.54	1.18	.500		Н	1	5/8	200.00 M		
N6974-2	16	1.019	5/16	11/4	.378	-	Н	13/16	1/4	210.00 M		
N6974-1	16	1.019	5/16	11/4	.442		Н	13/16	1/4	210.00 M		
N6461	16	1.019	.54	1.25	.500	_	Н	1	5/8	210.00 M		
N6939A	16	1.019	.54	1.25	.257°D'		NH	_	-	210.00 M		
N6939B	16	1.019	.54	1.25	.257	_	Н	1	1/4	210.00 M		
N6458	18	1.146	.54	1.36	.250	.062 x .030	NH	_		230.00 M		
N6459	18	1.146	.54	1.38	.500		Н	1	19/64	230.00 M		
N6463	19	1.210	.54	1.44	.500	_	Н	1	5/8	240.00 M		
N6711	20	1.273	13/32	1-23/64	15/64	-	NH		_	250.00 M		
N6485	20	1.273	.54	1.50	.250	.062 x .035	NH			250.00 M		
N6498	20	1.273	.54	1.45	.375	.094x .042	NH	_		250.00 M		
N6456	20	1.273	.54	1.50	.500	-	NHS	1	5/8	250.00 M		
N1010-22	22	1.401	.43	1.62	.312		Н	9/16	5/16	270.00 M		
N6454	23	1.464	.54	1.68	.250	.063 x .036	NH	7/ 10	3/ 10			
N6513	23	1.464	.54	1.68	.312			1/2	5/22	280.00 M		
N6465	23	1.464	.54	1.68	.500	-	NHS	1/2	5/32	280.00 M		
N5485-24	24	1.528	.31	1.56		_	Н	0/14	5/8	280.00 M		
N6462	24	1.528	-	the same of the same of	.250	-	Н	9/16	1/4	300.00 M		
N6708	28		.54	1.75	.500		NHS	1	5/8	300.00 M		
	-	1.783	13/32	1-57/64	.752	-	NH	-	-	350.00 M		
N6464	28	1.783	.54	2.00	.500	-	Н	1	5/8	350.00 M		
N1241	30	1.910	.24	1.95	.501	.090 x .040	NH		_	380.00 M		
N1208	35	2.228	9/32	2-5/16	.367		NH		-	440.00 M		
N1177	40	2.546	.54	2.77	.468	.094 x .045	Н	15/16	3/16	500.00 M		
N1178	42	2.674	.54	2.90	.312	.094 x .045	NHS	1/2	3/16	520.00 M		
N1176	48	3.056	.59	3.28	.500	$.094 \times .045$	NH	_		600.00 M		

^{*}This list includes all items on Pg. 17 of Catalog 55 with new prices effective immediately.

nylomatic division, nolan avenue, morrisville, pennsylvania, 19067 - telephone (215) 295-4151

CATALOG 55 SUPPLEMENT



		1/4" PIT	CH SPROCKET	S (Pg. 18)		
PART NO.	TEETH	O. D.	I.D.	HUB DIA.	HUB LENGTH	PRICE PLUS SET-UP
N6826	18	1.568	.374	0.750	.312	\$92.75 M

	PLAIN BEARINGS, WASHERS, STAND-OFFS (Pg. 19-22)												
PART NO.	I.D.	0.D.	Length	Price Plus Set-up		PART NO.	I.D.	0.D.	Length	Price Plus Set-up			
N6617	.088	5/32	1/16	\$11.20 M		N6834	.255	.375	.044	\$11.10 M			
ND17	.097	.220	.167	15.40 M		N6738	.255	.375	.540	11.70 M			
N6725	.098	.188	.045	10.00 M		ND31	.256	.514	.811	49.85 M			
N6732	.105	.170	.400	10.00 M		N6849	.255	7/16	. 062	10.50 M			
ND18	.115	7/16	1/8	16.35 M		N6686	.259	.751	.247	14.95 M			
ND47	.123	1/4	9/16	15.05 M		N6904	.315	5/8	.065	13.10 M			
N6680	.125	.178	7/32	10.00 M		N6892	.319	7/8	1/4	54.05 M			
N6645	.128	1-1/8	1/8	36.95 M		N6721-1	21/64	1	3/16	75.60 N			
ND72	.157	9/32	.125	17.35 M		N6795	.377	.497	2.018	37.50 N			
ND56	.184	3/8	3/4	18.30 M		N6948	.378	.750	1	36.75 N			
N6808	3/16	3/4	1/16	8.10 M		ND64	.382	47/64	1/16	15.00 N			
N6706	.191	7/16	1/16	11.70 M		ND53	.380	9/16	.160	22.10 N			
ND69	.194	.343	.031	16.50 M		N6749	.420	.657	.375	16.50 N			
N6338	.190	.627	.343	15.90 M		N6893	.506	1-1/8	3/16	55.30 N			
ND67	.196	.465	.265	15.40 M		ND89	.513	.730	.120	16.50 N			
ND84	.236	.302	.500	15.55 M		ND45	33/64	1-1/4	3/32	19.50 N			
ND33	.250	.520	.250	16.95 M		N1224	.521	2-3/8	3/16	95.70 N			
ND60	.250	.562	.062	15.40 M		ND42	39/64	1-3/32	1/8	25.90 N			
N6775	.255	.345	.546	10.70 M		ND35	.646	7/8	1/4	18.70			
N6938	.255	.375	.303	11.40 M		N6765	.757	1.001	.284	27.25 1			

nylomatic division, nolan avenue, morrisville, pennsylvania, 19067 - telephone (215) 295-4151


nylomatic

CATALOG 55 SUPPLEMENT



	FLANGED BEARINGS, INSULATORS, SLEEVES (Pg. 23-27)												
PART NO.	l:D.	O.D.	Flange Dia.	Flange Thick.	0.L.	Price + Set Up	PART NO.	I.D.	O.D.	Flange Dia.	Flange Thick.	0.L.	Price + Set Up
N6621	.021	.062	1/8	.015	.040	16.80 M	ND52	.210	.297	.420	.070	.610	15.15 M
ND36	5/64	3/16	1/4	1/16	1/8	15.05 M	ND83	.233	.302	.500	.090	.590	16.10M
ND65	.124	.166	.230	.030	.220	16.80 M	ND13	.252	.386	.502	.065	.875	17.90 M
ND63	.125	.240	.312	.078	.156	17.20 M	ND85	.261	.377	.485	.060	.380	33.80 M
N1102	.123	.342	5/8	1/16	1/4	15.40 M	ND61	.260	.353	.555	.060	.410	15.40 M
ND40	.130	.169	.250	.015	.025	15.20 M	ND1	.261	.379	.509	.062	.113	19.15 M
ND3	.130	.186	.254	.036	.952	43.70 M	ND51	.265	.508	1.000	.167	.385	48.55 M
ND95	.142	.191	1/2	.040	.095	15.10 M	N5665	.314	.433	5/8	1/16	7/16	21.90 M
ND28A	.144	.242	3/8	.253	15/16	17.10 M	ND92	.320	.365	1/2	5/8	7/8	19.30 M
ND75	.148	.186	.250	.015	.025	16.10 M	ND91	.318	.369	1/2	1-5/16	1-9/16	43.80 M
ND81	.159	.249	.312	.062	.250	18.55 M	ND82	.320	.441	.750	.068	.818	19.10 M
N199	.158	.217	1/2	.062	.312	23.60 M	ND94	.331	.385	.700	.030	.078	15.20 M
N6801	.170	.309	.375	1/16	1/8	15.30 M	N6743	.376	.501	.705	.063	.566	18.20 M
N6716	.172	.248	.308	.127	.320	15.80 M	N6921	.376	.623	.750	.125	.375	20.60 M
ND80	.191	.378	1/2	1/16	9/16	33.50 M	N2139	.379	.513	.750	.041	.258	55.20 M
N6771	.194	.363	.560	.064	.703	17.70 M	ND14	.388	.508	.630	.070	.875	19.30 M
N6883	.198	.250	.500	.032	.100	17.00 M	ND79	.521	.617	.740	.160	.472	19.10M
N6740	.198	.374	1/2	7/16	9/16	13.25 M	N6937	.544	.723	.800	.035	.160	18.85 M
N5890	.206	.315	.431	.091	.146	16.75 M	N6902	.629	.878	1.258	.072	.777	39.60 M
ND26	.209	.319	5/8	.048	9/64	17.00 M	ND21	.759	1.002	1.485	.100	.580	38.50 M

CATALOG 55 SUPPLEMENT



	ROLLERS - SOLID & CORED (Pg. 28)												
PART NO.	TYPE	0.D.	WIDTH	I.D.	0. L.	PRICE PLUS SET-UP							
ND33	А	.520	.250	.250		\$16.95 M							
N6338	А	.627	.343	.190	-111	12.46 M							
N6686	Α	.751	.247	. 259	_	11.15 M							
N6892	А	7/8	1/4	.319	_	54.05 M							
N6936	F	3/4	3/8	.255	5/8	21.35 M							

	PLAIN	& FLAN	GED ROL	LERS WIT	гн соинт	ER BORE	S (Pg. 30)		
PART	TVDE		0.0	COUNTE	ER BORE	FLANGE		0.1	PRICE
NO.	TYPE	I.D.	0.D.	DIA.	DEPTH	DIA.	THICK	O.L.	PLUS SET-UF
N6672		.316	.875	1/2	7/32			13/16	\$57.60 M
N6872	X	.315	.900	5/8	1/8	1-13/16	7/32	.450	80.70 M
N6741	Υ	.130	5/16	1/4	1/16	15/32	9/64	11/64	8.20 M
N5109	Y	.315	.376	.387	.036	.563	.063	.150	7.00 M

	BOBBINS & SPOOLS (Pg. 31)											
PART NO.	TYPE	FLANGE DIA.	FLANGE THICK	I.D.	0.D.	OAL.	PRICE PLUS SET-UP					
N6709	A	1/2	3/64	.190	5/16	1,1/16	\$27.65 M					
*N6573	A	5/8	. 030	.168	3/8	.362	51.20 M					
N1184	А	1-3/8	.040	.254	15/16	41/64	95.60 M					
N1228	A	1-3/8	1/16	21/32	7/8	1-3/16	109.40 M					

^{*}Has a 9/32 dia. x .020 hub on one side.

nylomatic division, nolan avenue, morrisville, pennsylvania, 19067 - telephone (215) 295-4151

nylomatic


CATALOG 55 SUPPLEMENT



	R	RIVETS, BU	TTONS, PLU	JGS (Pg. 32)		
PART NO.	HEAD TYPE	SHANK DIA.	SHANK LENGTH	HEAD DIA.	HEAD THICK	PRICE PLUS SET-UP
N6540R	А	.160	3/16	5/16	.125	\$ 5.30 M
N6685R	В	.058	3/32	3/32	.025	4.20 M
N5705	С	.079	.104	.147	.023	4.40 M
N183R	С	.147	.187	.375	.036	18.35 M
N6705R	С	.188	13/32	7/16	3/32	11.15 M
N6669	D	.070	.047	.125	.109	13.40 M
ND78R	D	.092	.090	.155	.058	15.55 M
N6993	D	.134	.140	.250	.080	5.10 M
N6622	D	.193	1/8	1/2	1/8	9.90 M

PULLEYS (Pg. 33)											
PART NO.	TYPE	OUTER DIA.	SLOT DIA.	SL:OT WIDTH	OVERALL WIDTH	BORE	PRICE PLUS SET-UP				
N5727	Α	5/8	5/16		7/32	.064	\$ 21.75 M				
N6539	A	.875	.656	.125	.406	.194	46.40 M				
N6832	А	1-1/8	.718	.040	.232	.177	40.45 M				
N5860	В	.378	.299	.076	.182	-	20.25 M				
N6396	D	.500	.370	.103	.143	.127	94.80 M				
N6855	D	1.245	.960	.125	. 245	.254	37.35 M				
N6946	D	1-3/8	1-3/16	1/8	3/16	.191	58.80 M				

nylomatic division, nolan avenue, morrisville, pennsylvania, 19067 - telephone (215) 295-4151



SPECIFICA.

Catalog Page		Supplement Page
3	GENERAL SPECIFICATIONS	••
4	ENGINEERING KITS	••
5	16 PITCH GEARS	A
6	24 PITCH GEARS	A
7	32 PITCH PLAIN GEARS	A
8	32 PITCH GEARS WITH HUBS	А
9	48 PITCH PLAIN GEARS	В
10	48 PITCH GEARS WITH HUBS	В
11	MISCELLANEOUS GEARS 14½° AND 20° PA	В
12	32 PITCH COMBINATION GEARS	В
13	48 PITCH COMBINATION GEARS	В
14	MISCELLANEOUS COMBINATION GEARS	8
15 and 16	MISCELLANEOUS MITER GEARS AND ANGLE GEARS	66.
17	TIMING BELT PULLEYS 1/5" PITCH	C
18	1/4" PITCH SPROCKETS	D
19 thru 22	PLAIN BEARINGS	D
23 thru 27	FLANGED BEARINGS	E
28 thru 30	ROLLERS	F
31	BOBBINS	F
32	RIVETS	
33	PULLEYS	
34	SHOULDER WASHERS	
35	STAMPED WASHERS	••
36 thru 38	MISCELLANEOUS FASTENERS	
39 thru 42	MISCELLANEOUS MOLDED PARTS	
43	PHYSICAL PROPERTY CHART	
44	NOTES	a.c

Many standard parts can be

injection molded parts

Materials

Standard material is DuPont type #101 natural color nylon. Many standard parts can be molded of Delrin* at no change in price; also other materials and colors are available; prices upon application.

Tolerances

Tolerances on decimals are $\pm .005$ per inch of dimension with a minimum of $\pm .002$. except dimensions marked (†) carry a minimum of ±.003. Tolerances on all fractional dimensions are $\pm .015$ per inch of dimension. Total indicated runout is .010 per inch of dimension.

Pricing and Terms

Add a \$25.00 set-up charge to each item listed. All prices are subject to change without notice. Terms on production are 1% 10 days, net 30 days F.O.B. Morrisville, Pa. (*Reg. trade name-DuPont Co.)

stamped parts

Materials

Stamped parts are available in type #101 Nylon, Delrin*, Nylatron GS**, polyethylene and Teflon*. The standard thicknesses are .031", .047", .062", .093" and .125". (*Reg. trade name—DuPont Co. **Reg. trade name—Polymer Corp.)

Commercial tolerances on O.D. and I.D. are $\pm .004$ ". Closer tolerances available by construction of special dies at extra cost. Material tolerances are based on standard mill tolerance. Rule of thumb from 5 to 10% plus or minus. Available in closer tolerances on special order at extra cost.

Slight burrs are inherent on high speed punchings. In some cases these burrs can be removed by tumbling but with abrasion resistant materials such as nylon some burrs must be expected. If the edges must be smooth the parts should be produced by machining or molding.

Flatness

As washers are stamped from coiled strips they very often will not be flat. This condition becomes more pronounced as the thickness of material increases.

Standard Sizes

The sizes listed are available without tooling charges. Intermediate sizes can be supplied but may involve a nominal charge for special tooling.

Prices of stamped parts are quoted upon application. Please state the size, thickness, material and quantity required.

IF YOU DON'T SEE WHAT YOU WANT, LET NYLOMATIC QUOTE ON PRO-DUCTION TO YOUR SPECIFICATIONS FROM PATENTED LOW-COST TOOLING.

save TIME save MONEY with this new design tool . . .

NYIOMATIC ENGINEERING KITS



KIT. NO.	CONTENTS	PRICE
G-1-16	2 ea. 16 Pitch Gears listed on page 5	\$20.00
G-1-24	2 ea. 24 Pitch Gears listed on page 6	15.00
G-2-32	2 ea. 32 Pitch Plain Gears listed on page 7	15.00
G-3-32H	2 ea. 32 Pitch Gears with Hubs listed on page 8	16.50
G-4-48	2 ea. 48 Pitch Plain Gears listed on page 9	15.00
G-5-48H	2 ea. 48 Pitch Gears with Hubs listed on page 10	15.0
G-7-M	2 ea. Miscellaneous Gears 14½° and 20° PA listed on Page 11	15.0
G-8-32C	2 ea. 32 Pitch Combination Gears listed on page 12	15.0
G-6-48C	2 ea. 48 Pitch Combination Gears listed on page 13	15.0
G-9-C	2 ea. Miscellaneous Combination Gears listed on page 14	15.0
G-8-M	2 ea. Miscellaneous Miter Gears and Angle Gears listed on pages 15 and 16	15.0
BP-2	2 ea. Timing Belt Pulleys 1/5" Pitch listed on page 17	27.0
SP-4	2 ea. 1/4" Pitch Sprockets listed on page 18 except those marked †	15.0
WSB-1	2 ea. Plain Bearings listed on page 19	12.0
WSB-2	2 ea. Plain Bearings listed on page 20	12.0
WSB-3	2 ea. Plain Bearings listed on page 21	12.0
WSB-4	2 ea. Plain Bearings listed on page 22 except those marked *	10.0
FB-1	2 ea. Flanged Bearings listed on page 23	15.0
FB-2	2 ea. Flanged Bearings listed on page 24	15.0
FB-3	2 ea. Flanged Bearings listed on page 25	15.0
FB-4	2 ea. Flanged Bearings listed on page 26	15.0
FB-5	2 ea. Flanged Bearings listed on page 27	18.0
RW-1	2 ea. Rollers listed on page 28	20.0
RW-2	2 ea. Rollers listed on pages 29 and 30	15.0
MB-2	2 ea. Bobbins listed on page 31	15.0
TF-3	4 ea. Teflon Shoulder washers listed on page 34	15.0
RBP-1	4 ea. Rivets listed on page 32	14.0
P-1	2 ea. Pulleys listed on page 33	15.0
SW-1	6 ea. Washers 1/8" - 3/8" listed on page 35	15.0
SW-2	6 ea. Washers 7/16" - 11/16" listed on page 35	15.0
SW-3	6 ea. Washers 3/4" - 1" listed on page 35	15.0
SW-4	6 ea. Washers 1 1/8" - 2 3/8" listed on page 35	15.0
GR-1	4 ea. Gear Racks	14.0

nylomatic division, morrisville, bucks county, pennsylvania


nylomatic




- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.









STYLE H

STYLE NH

			141/	PRESS	SURE A	NGLE			
PART NO.	P. A.	TEETH	HOLE A	P. D.	STYLE	H DIA. C	UB PROJ. D	FACE B	PRICE PLUS SET-UF
N5793	141/2	12	.249	.750	Н	.430	.028	.225	\$ 47.00 M
N6589	141/2	16	.252	1.000	Н	3/4	5/16	.375	84.00 M
N5626	141/2	20	1/2	1.25	Н	.865	1/2	.318	109.59 M
N6171	141/2	30	.986	1.875	Н	1.602	.500	.875	257.30 M
N1.004-1	141/2	36	.375	2.25	н	3/4	3/8	.320	310.40 M
N1109*	141/2	42	.400	2.625	Н	1.360	1/4	.625	324.80 M
N1143A	141/2	42	.850	2.625	Н	1 3/8	1/4	5/8	395.25 M

20° PRESSURE ANGLE 92 .750 NH

N5896	20	12	.192	.750	NH	-		.095	\$ 46.37 M
N6209	20	30	.367	1.875	Н	.990	.500	.379	179.79 M
N1166	20	34	.365	2.12	Н	1	.510	.375	264.23 M
□N1165	20	76	1/2	4.75	Н	7/8	1/4**	3/8	1204.00 M
□N1126	20	80	1/2	5.00	Н	7/8	1/4**	3/8	1240.00 M

^{*} Has a .126 wide keyway

Issued 6-69

nylomatic division, morrisville, bucks county, pennsylvania

[☐] Available only in glass filled Delrin Matl. \$50.00 set-up charge.

^{**} Has a 1/4" extension each side




nylomatic 24 PITCH SPUR GEARS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.



Tooth Size



STYLE H

STYLE NH

			14½° PRE	SURE A	NGLE			
PART NO.	TEETH	P. D.	HOLE	STYLE	FACE B	DIA. C	JB PROJ. D	PRICE PLUS SET-UP
N6004	12	.500	.250 x .192(D)	Н	.256	.398	.188	\$ 47.48 M
N5828-12	12	.500	.252	Н	.318	.370	.250	48.58 M
N5602-1	15	.625	.250	NH	.220			48.12 M
N2045-1	18	.75	.250 x .192(D)	Н	1/4	1/2	3/16	52.88 M
N2045-2	18	.75	.253	Н	1/4	1/2	3/16	52.88 M
N2045-3	18	.75	.253	Н	1/4	.442	7/16	53.87 M
N2045-4	18	.75	.250	Н	1/4	1/2	.095	52.12 M
N2045-5	18	.75	.250	Н	1/4	1/2	1/4	53.00 M
N5851	18	.75	.250 x .215(D)	Н	.256	.493	.250	53.00 M
N240	21	.875	.377 x .318(D)	Н	1/4	5/8	5/16	58.88 M
N297	24	1.00	.252	Н	1/4	5/8	3/16	59.20 M
N5515	24	1.00	.256	Н	1/4	5/8	3/8	42.10 M
N417	27	1.125	.314	NH	.183	.=:	_	33.30 M
N6290	36	1.500	.249	NH	.093	_	_	69.49 M
N5425	40	1.667	.125	Н	.047	1/2	1/8	66.43 M
*N1044	84	3.50	.378	Н	.325	.850	.230	582.00 M
			20° PRES	SURE A	NGLE			
N6530	18	.75	.304	Н	1/4	1/2	1/8	\$ 27.79 M
N5774	24	1.00	.256	NH	3/8		_	57.83 M
N6274	36	1.50	.250	NH	1/8	3/8	1/16	79.48 M
N5775	36	1.50	.310	н	3/8	.738	.250	89.71 M

^{* \$50.00} set-up charge.

nylomatic 32 PITCH SPUR GEARS — PLAIN




- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.

32 Pitch

Actual Tooth Size

Issued 6-69



		141/2° PRESS	SURE ANGLE		
PART NO.	TEETH	P. D.	HOLE	FACE B	PRICE PLUS SET-UP
N32-12	12	.375	.125	3/16	\$ 45.50 M
N32-14	14	.438	.125	3/16	45.94 M
N6097	14	.438	.127	3/16	45.94 M
N6548	14	.438	.188 sq	3/16	45.94 M
N32-16	16	.500	.190	3/16	46.37 M
N32-18	18	.563	.190	3/16	46.83 M
N32-20	20	.625	.190	3/16	47.48 M
N32-24	24	.750	.190	3/16	49.25 M
N5594	24	.750	.252	.177	49.25 M
N32-28	28	.875	.190	3/16	50.80 M
N32-32	32	1.000	.250	3/16	52.32 M
N32-36	36	1.125	.250	3/16	53.50 M
N5832	36	1.125	.313	.382	62.93 M
N32-38	38	1.188	.250	3/16	71.76 M
N32-40	40	1.250	.250	3/16	73.75 M
N32-44	44	1.375	.250	3/16	76.77 M
N32-48	48	1.500	.250	3/16	80.55 M
N2096	48	1.500	.500	3/16	80.55 M
N32-52	52	1.625	.250	3/16	83.21 M
N5404	56	1.750	.624	.192	77.53 M
N32-56	56	1.750	.250	.194	95.00 M
N32-62	62	1.938	.250	.198	102.00 M
N6186	62	1.938	.927	.250	97.27 M




32 PITCH SPUR GEARS — WITH HUBS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.

32 Pitch





			14½° F	RESSURE	ANGLE			
DART			HOLE		FACE	Н	UB	PRICE
PART NO.	TEETH	P. D.	A	STYLE	В	DIA. C	PROJ. D	PLUS SET-UP
N32-12H	12	.375	.125	Н	3/16	1/4	3/16	\$ 46.05 M
N6098	12	.375	.188	Н	3/16	.279	.188	46.05 M
N32-14H	14	.438	.125	Н	3/16	5/16	1/4	46.50 M
N32-16H	16	.500	.188	Н	3/16	3/8	1/4	48.17 M
N5331	16	.500	.256	Н	3/16	.406	.250	48.17 M
□N5484	18	.563	.252	Н	3/16	.462	.250	48.87 M
N32-18H	18	.563	.188	Н	3/16	3/8	1/4	48.87 M
N5015-2	20	.625	.255	Н	.185	.487	.195	49.25 M
N32-20H	20	.625	.188	Н	3/16	1/2	1/4	50.43 M
□N5828-20	20	.625	.248	Н	3/8	.488	.185	52.16 M
□N5490-3	22	.688	.252	Н	.188	.563	.250	52.56 M
N32-24H	24	.750	.188	Н	3/16	5/8	1/4	51.87 M
□N5486-26	26	.813	.250	Н	.250	.563	.250	56.30 M
□N5489-G	26	.813	.313	Н	.250	.563	.250	56.30 M
N32-28H	28	.875	.188	Н	3/16	5/8	1/4	53.42 M
N2075	32	1.000	.192	Н	.260	.312	.312	56.97 M
N32-32H	32	1.000	.250	Н	3/16	5/8	1/4	54.52 M
N32-36H	36	1.125	.250	Н	3/16	5/8	1/4	56.05 M
□N5486-38	38	1.188	.252	Н	.250	.563	.250	77.78 M
□N1010G	40	1.250	.313	Н	.250	.563	.250	80.06 M
N32-40H	40	1.250	.250	Н	3/18	5/8	1/4	76.77 M
N5880	40	1.250	.316	Н	1/2	.620	.125	96.26 M
N32-44H	44	1.375	.250	Н	3/16	5/8	1/4	79.40 M
N32-48H	48	1.500	.250	Н	3/16	5/8	1/4	88.60 M
N32-52H	52	1.625	.250	Н	3/16	5/8	1/4	98.10 M
N5829	52	1.625	.250	Н	3/8	.504	.185	109.03 M
N32-62H	62	1.938	.250	Н	.198	5/8	3/8	109.59 M
N6187	62	1.938	.375	Н	.250	.614	.375	130.48 M

☐ Hub has a .102 dia. cross hole.

nylomatic division, morrisville, bucks county, pennsylvania

nylomatic 48 PITCH SPUR GEARS – PLAIN





- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.

48 Pitch

M

Actual Tooth Size







STYLE NH

DD HOLE

SQUARE HOLE

		1-	4½° PRESSURE ANG	LE		
PART NO.	TEETH	P. D.	HOLE A	STYLE	FACE B	PRICE PLUS SET-UP
N48-12	12	.250	.094	NH	.125	\$44.60 M
N363-3	12	.250	.145 Dia. x .110 DD	NH	.112	44.60 M
N48-14	14	.292	.094	NH	.125	44.83 M
N48-16	16	.333	.125	NH	.125	45.04 M
N6510	16	.333	.125 NH		.125	45.10 M
N48-18	18	.375	.125	NH	.125	45.27 M
N338	18	.375	.125	NH	.100	42.69 M
N48-20	20	.417	.125	NH	.125	45.50 M
N363-2	20	.417	.145 Dia. x .110 DD	NH	.112	45.50 M
N48-24	24	.500	.125	NH	.125	45.94 M
N48-28	28	.583	.125	NH	.125	46.37 M
N48-32	32	.667	.125	NH	.125	47.04 M
N6511	32	.667	.250	NH.	.125	47.00 M
N48-36	36	.750	.188	NH	.125	47.70 M
N6011-36	36	.750	.315 Square	NH	.157	47.48 M
N6011-40	40	.833	.204	NH	.188	48.80 M
N48-40	40	.833	.188	NH	.125	48.80 M
N363-1	44	.917	.190" Square	NH	.112	47.70 M
N48-48	48	1.000	.188	NH	.125	50.35 M
N48-56	56	1.167	.188	NH	.125	66.22 M
N48-60	60	1.250	.250	NH	.125	67.48 M
N5715	60	1.250	.253	NH	.312	74.78 M
N48-64	64	1.333	.250	NH	.125	70.00 M
N48-72	72	1.500	.250	NH	.125	73.70 M
N48-80	80	1.667	.250	NH	.125	76.40 M




48 PITCH SPUR GEARS — WITH HUBS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.

48 Pitch

Actual Tooth Size



STYLE H

	14½° PRESSURE ANGLE										
			•	7		н	UB				
PART NO.	TEETH	P. D.	HOLE A	STYLE	FACE B	DIA. C	PROJ. D	PRICE PLUS SET-UP			
N48-12H	12	.250	.094	Н	.125	3/16	3/16	\$45.02 M			
N48-14H	14	.292	.094	Н	.125	1/4	3/16	45.38 M			
N48-16H	16	.333	.125	Н	.125	1/4	3/16	45.58 M			
N48-18H	18	.375	.125	Н	.125	5/16	3/16	46.10 M			
N48-20H	20	.417	.125	Н	.125	3/8	1/4	47.21 M			
N48-24H	24	.500	.125	Н	.125	3/8	1/4	49.38 M			
N48-28H	28	.583	.125	Н	.125	1/2	1/4	49.83 M			
N48-32H	32	.667	.125	Н	.125	1/2	1/4	50.50 M			
N48-36H	-36	.750	.188	Н	.125	5/8	1/4	52.02 M			
N335	40	.833	.125	Н	.115	3/8	3/16	49.68 M			
N48-40H	40	.833	.188	Н	.125	5/8	1/4	53.12 M			
N48-48H	48	1.00	.188	Н	.125	5/8	1/4	54.66 M			
N48-56H	56	1.167	.188	Н	.125	5/8	1/4	71.28 M			
*N5615	60	1.250	.250	Н	.125	1	.25	77.90 M			
N48-60H	60	1.250	.250	Н	.125	5/8	1/4	71.80 M			
N48-64H	64	1.333	.250	Н	.125	5/8	1/4	74.40, M			
N48-72H	72	1.500	.250	Н	.125	5/8	1/4	76.77 M			
N48-80H	80	1.667	.250	Н	.125	5/8	1/4	80.20 M			
N5617	96	2.000	.250	Н	.125	1	1/4	93.80 M			


^{*}Has a hub $1/2 \times 1/4$ Projection on opposite side of gear.

nylomatic

MISCELLANEOUS GEARS 14½° AND 20° P.A.

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.





			141/2	° PRESS	URE A	NGLE			
PART NO.	PITCH	TEETH	HOLE A	P. D.	STYLE	H DIA. C	UB PROJ. D	FACE B	PRICE PLUS SET-UP
*N5013	12	16	.625	1.333	н	7/8	9/32	.487	\$ 76.85 M
N5017	12	18	1/4	1.500	NH	_		.404	71.10 M
N1142	12	30	.610	2.500	н	1"	5/8	.615	395.25 M
N1116-1	20	24	.315	1.20	Н	.860	5/16	.375	184.16 M
N1116-2	20	24	.495	1.20	Н	.860	5/16	.375	176.90 M
N1040	28	71	.610	2.536	NH.	_	-	.255	171.60 M
N1040H	28	71	.625	2.536	Н	1.250	.370	.255	177.60 M
N308	56	36	092	.643	Н	5/16	1/16	.125	26.22 M
N330	64	32	.099 dia. × .084 A.F.	.496	NH		_	.085	14.90 M
N337	64	32	.093	.496	Н	.17	.046	.050	14.48 M
N205	64	60	.125	.938	Н	1/2	1/8	.125	51.24 M
			20°	PRESSI	URE AN	NGLE			
N5453	10	12	.480	1.2	NH	_	_	1.072	\$143.28 M
N6610	12	16	.600	1.333	NH	(<u></u>)	_	13/16	128.80 M
N1191	12	26	1.312	2.166	NH	_	_	13/16	256.00 M
N6204	20	20	.215	1.000	Н	.423	.500	1/4	81.64 M
N6203	20	24	.375	1.200	Н	5/8	1/2	1/4	86.40 M
*N6333	20	30	.875	1.500	NH	#95 - 186	_	3/8	104.55 M
N6176	20	30	.255	1.500	Н	5/8	1/8	.1875	80.31 M
N6555	32	34	.244	1.062	Н	.532	.185	1/8	43.98 M
N5138	40	35	.187	.875	NH	-	_	1/8	28.65 M
N6275	36	9	.124 D.D.	.250	Н	.187	.015	1/8	51.10 M
N6416	64	48	.185	.750	NH	_	_	.180	61.30 M

^{*}Has Counterbore

Issued 6-69

nylomatic division, morrisville, bucks county, pennsylvania




nylomatic 32 PITCH COMBINATION GEARS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.

32 Pitch

Tooth Size



		PINIO	٧				GEAR					
PART NO.	PITCH	TEETH	P.D.	FACE A	HOLE B	P.A.	PITCH	TEETH	P.D.	FACE C	P.A.	PRICE PLUS SET-UP
N318	32	8	.24	.203	.128	141/2	32	34	1.063	.158	141/2	\$ 52.12 M
N217	32	8	.24	.260	.125	141/2	48	60	1.25	.125	141/2	54.10 M
N6258	32	15	.469	5/16	.312	20°	32	64	2.000	1/4	20°	114.63 M
N6471-1	32	16	.500	3/16	.250	141/2	32	20	.625	3/16	141/2	70.64 M
N6512-1	32	16	.500	3/16	.250	141/2	32	22	.687	3/16	141/2	66.40 M
N6471-2	32	16	.500	3/16	.250	141/2	32	24	.750	3/16	141/2	72.10 M
N6512-2	32	16	.500	3/16	.250	141/2	32	26	.812	3/16	141/2	74.60 M
N6471-3	32	16	.500	3/16	.250	141/2	32	28	.875	3/16	141/2	76.80 M
N6512-3	32	16	.500	3/16	.250	141/2	32	30	.937	3/16	141/2	81.60 M
N1182-1	32	16	.500	3/16	.250	141/2	32	36	1.125	3/16	141/2	146.72 M
N32-16-40	32	16	.500	.180	.254	141/2	32	40	1.25	.195	141/2	57.84 M
N1182-2	32	16	.500	3/16	.250	141/2	32	44	1.375	3/16	141/2	158.20 M
N1182-3	32	16	.500	3/16	.250	141/2	32	48	1.500	3/16	141/2	176.60 M
N5445	32	18	.562	.310	.180	141/2	48	48	1.00	.16	141/2	61.80 M
N6318	32	32	1.000	3/16	.248	141/2	32	48	1.500	3/16	141/2	96.18 M

nylomatic48 PITCH COMBINATION GEARS




- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.

48 Pitch

Actual Tooth Size

Issued 6-69




14½° PRESSURE ANGLE								
PART NO.	PINION TEETH (B)	GEAR TEETH (A)	PRICE PLUS SET-UP					
N48-12-36	12	36	\$48.36 M					
N48-12-40	12	40	49.02 M					
N48-12-48	12	48	50.46 M					
N48-12-56	12	56	62.38 M					
N48-12-60	12	60	64.00 M					
N48-12-64	12	64	65.70 M					
N48-12-72	12	72	66.48 M					
N48-12-80	12	80	67.24 M					
N48-14-36	14	36	47.37 M					
N48-14-40	14	40	49.44 M					
N48-14-48	14	48	51.60 M					
N48-14-56	14	56	64.50 M					
N48-14-60	14	60	65.36 M					
N48-14-64	14	64	65.94 M					
N48-14-72	14	72	70.20 M					
N48-14-80	14	80	74.44 M					
N48-16-36	16	36	49.25 M					
N48-16-40	16	40	50.94 M					
N48-16-48	16	48	52.62 M					
N48-16-56	16	56	65.16 M					
N48-16-60	16	60	66.64 M					
N48-16-64	16	64	68.10 M					
N48-16-72	16	72	71.81 M					
N48-16-80	16	80	75.44 M					

nylomatic division, morrisville, bucks county, pennsylvania



MISCELLANEOUS COMBINATION GEARS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.



		PINION	1				GEAR					
PART NO.	PITCH	TEETH	P.D.	FACE A	HOLE B	P.A.	PITCH	TEETH	P.D.	FACE C	P.A.	PRICE PLUS SET-UP
N5602-2	24	12	.50	.250	.255*	141/20	24	30	1.25	.225	141/20	\$ 62.90 M
N5721	24	14	.583	.550	.255	20°	24	24	1.00	.375	20°	67.35 M
N6102	24	15	.625	.359	.250	20°	24	36	1.50	.187	141/20	70.00 M
N6444	48	9	.187	.160	.096	141/20	48	40	.833	1/16	141/20	51.10 M
N6531	48	12	.250	.218	.126	14½°	48	36	.750	1/8	141/20	53.60 M
N5157	48	12	.25	.140	.130	·14½°	48	40	.833	.100	141/20	54.10 M
N5744	48	16	.333	.25	.125	141/20	48	60	1.25	.125	141/20	55.44 M
N5717	48	18	.375	.563	.130	141/20	48	54	1.125	.125	141/20	55.86 M
N5702	48	20	.417	.188	.257	141/20	48	60	1.25	.125	141/20	54.54 M
N5726	48	20	.417	.188	.257	141/20	48	80	1.667	.125	141/20	61.35 M
TO THE SECOND	48	30	.625	.125	.250	141/20	48	48	1.00	.125	141/20	74.35 M
N6234 N6251	48	35	.729	.065	.220	20°	48	80	1.667	.095	20°	79.12 M

^{*}Counterbored hole (.375 x .1 dp.)


nylomatic


MITER GEARS — 90° AND GEAR CLUSTERS




- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.











TYPE X

TYPE Z

20° PRESSURE ANGLE										
PART NO.	P.D.	PITCH	TEETH	HOLE A	TYPE	MOUNTING DISTANCE		HUB DIA. B	PRICE PLUS SET-UP	
N6093-1	.500	32	16	.095	Z	.344	.192	.250	\$ 45.27 M	
N6093-2	.500	32	16	.158	Х	.813	.678	.250	47.08 M	
N174	.5	32	16	.156	X	.525	.356	.408	43.20 M	
N361	.5	64	32	.192	X	.563	.432	.365	46.37 M	
N5346	.60	20	12	D ¼ x .195	Х	.67	.460	.520	47.82 M	
N5613	1.0	24	24	DD 38 x .25	Х	1.125	.781	.688	62.90 M	
N2023	1.0	24	24	1/4	Υ	SEI	DIAGRA	M	59.20 M	
N1048	2.200	10	22	.995	Х	1.99	1.310	1.510	450.00 M	








FIG. A

FIG. B

FIG. C

<u> </u>			14½°	PRESSU	JRE AN	GLE			
PART NUMBER OF TEETH									PRICE
NO.				2	3	4	5	6	PLUS SET-UP
N5762	A	32	48	36	18	12	-		\$86.12 N
N5698	В	48	60	48	36	24	12		74.64 N
N5699	С	48	48	40	32	24	16	12	66.92 M

nylomatic division, morrisville, bucks county, pennsylvania



MISCELLANFOUS GEARS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.


092. X 8MH

ANGLE DRIVE GEARS

45° Helix Angle R.H.

A. 24 D.P. B. 24 D.P. 24 Teeth 12 Teeth 1.00 P.D. .50 P.D. 14½° P.A. 14½° P.A.

N5224 \$71.64 M PAIRS + Setup



N333

48 Pitch

.300 P. D.

WORM (B)


Single Thread

N334 WORM GEAR (A)

48 Pitch 16 Teeth .332 P. D. Helix 3°-49'

Helix 3°-49′ R. H. 20° P.A R. H. 20° P.A. Ratio 1:16


N333-334 \$40.00 M PAIRS + SETUP



BEVEL GEAR

12 Pitch, 24 Teeth, 20° P.A.


N1087 \$164.22 M + SETUP



BEVEL GEAR


12 Pitch, 12 Teeth, 20° P.A.

N6019 \$73.14 M + SETUP




N5373 \$63.36 M + SET-UP

12 Pitch 12 Teeth




N2011 \$55.40 M + SETUP




BEVEL GEARS 48 Pitch

N442 \$64.80 M PAIRS + SET-UP



320 1.686 O.D. 1.624 D.D. 1.636 D.D. 1.626 D





Issued 6-69

nylomatic †" PITCH TIMING BELT PULLEY!



- Tolerances ±.005 per inch of dimension
- A set-up charge of \$25.00 is made each time a part is ordered.
- Standard material is Nylon, Delrin and Glass filled Delrin, except those marked *.
- Apply for prices on quantities larger than 5M pieces.
- Prices subject to change without notice.





NOTE: Nylomatic Corporation manufactures only the Timing Belt Pulleys. The required belts are manufactured by the U. S. Rubber Co.

	PART			FLANGE			8			UB	PRICE
	NO.	GROOVES	P. D.	O. D.	Α	I.D.	STYLE	KEYWAY	DIA. C	PROJ. D	PLUS SET-UP
	N5490-10	10	.637	.85	.31	.250	Н		9/16"	1/4"	
	N6449	11	.700	.93	.54	.250	NH				
•	N6452	11	.700	.92	.54	.312	Н	.094 x .045	1/2"	5/32"	
•	N6448	12	.764	.98	.54	.312	Н	.094 x .045	1/2"	5/32"	
	N6483	12	.764	.98	.54	.250	NH	.062 x .030			4.5
	N6497	12	.764	.94	.54	.375	NH	$.094 \times .045$			O
	N5490-12	12	.764	.92	.31	.250	Н		9/16"	1/4"	ш :
	N5489-12	12	.764	.92	.43	.312	Н		9/16"	1/4"	5
•	N6451	13	.828	1.04	.54	.400	NH	.094 x .045			A
•	N6455	14	.891	1.11	.54	.250	NH	.062 x .040			4
	N5490-14	14	.891	1.11	.43	.250	Н		9/16"	1/4"	
	N6460	15	.955	1.18	.54	.500	Н		1"	5/8"	5
	N6461	16	1.019	1.25	.54	.500	Н		1"	5/8"	Z W
	N6458	18	1.146	1.36	.54	.250	NH	.062 x .030			
	N6459	18	1.146	1.38	.54	.500	Н		1"	19/64"	
	N6463	19	1.210	1.44	.54	.500	Н		1"	5/8"	LEM
	N6456	20	1.273	1.50	.54	.500	NHS		1"	5/8"	В
•	N6485	20	1.273	1.50	.54	.250	NH	.062 x .035			4
•	N6498	20	1.273	1.45	.54	.375	NH	.094 x .042			2
	N1010-22	22	1.401	1.62	.43	.312	Н		9/16"	5/16"	S
	N6454	23	1.464	1.68	.54	.250	NH	.063 x .036			ш
	N6513	23	1.464	1.68	.54	.312	NHS		1/2"	5/32"	Ш
	N6465	23	1.464	1.68	.54	.500	Н		1"	5/8"	S
	N6462	24	1.528	1.75	.54	.500	NHS		1"	5/8"	
	N5485-24	24	1.528	1.56	.31	.250	Н		9/16"	1/4"	
	N6464	28	1.783	2.00	.54	.500	Н		1"	5/8"	
•	N1177*	40	2.546	2.77	.54	.468	Н	.094 x .045	15/16"	3/16"	
•	N1178*	42	2.674	2.90	.54	.312	NHS	$.094 \times .045$	1/2"	3/16"	
•	N1176*	48	3.056	3.28	.59	.500	NH	.094 x .045			


^{*} Available in Glass Filled Nylon only.



1/4" PITCH SPROCKETS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.





PART NO.	TEETH	O.D.	I.D.	HUB DIA.	HUB LENGTH	PRICE PLUS SET-UP
N6174	7	.590	.125	.250	.540	\$ 60.10 M
N6174-1	7	.590	.125	.250	.125	60.60 M
N6174-2	7	.590	.125	.250	.255	60.90 M
N5728	10	.919	.260 x .205 "D"	.500	.520	71.10 M
N5728-1	12	1.083	.260 x .190 "D"	.620	.520	76.01 M
N6529	12	1.083	.247	.437	.261	79.34 M
N6556	12	1.083	.495	.687	.085	79.10 M
N6558	12	1.083	.246	.434	.192	79.86 M
N5736	12	1.083	.312	.620	.510	81.67 M
N5737	15	1.297	.254	.617	.510	86.22 M
*N6286	17	1.487	.500	1.050 & .925	.270	89.77 M
N6826	18	1.568	.250	1.125	.500	92.75 M
N6391	21	1.809	.700	1.370	.420	95.92 M
N6006-1	24	2.049	.125	.490	.140	98.61 M
N6157	24	2.049	1.338	1.610	.400	106.20 M


^{*}Hub on both sides.


nylomatic


PLAIN BEARINGS, WASHERS, STAND-OFFS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.









PART NO.	A HOLE	B O.D.	C LENGTH	PRICE PLUS SET-UP	
N6170	.076	.110	.108	\$ 7.40 M	
N6366	.080	.120	.025	7.70 M	
N5803	.080	.250	.058	4.37 M	
N5259A	.086	.182	.561	5.02 M	
N5042	.094	.186	.188	4.37 M	
N5229A	.094	.190	.074	4.37 M	
NFL-24	.098	.192	.190	8.38 M	
N5348	.103	.485	.361	11.60 M	
N5584	.105	.378	.186	5.52 M	
N6075	.106	.194	.022	4.37 M	
N5382	.107	.154	.042	4.37 M	
NFL-4	.110	.220	.125	8.28 M	
N5854-1	.122	.370	.218	25.56 M	
N350	.122	.253	.118	7.62 M	
N457	.122	.180	.113	4.37 M	
N6421	.123	.251	.190	6.79 M	
N5854-2	.125	.306	.185	14.70 M	
N5210	.130	.251	.158	4.82 M	
N5143	.130	.248	.205	4.60 M	
N5349	.130	.247	.300	5.02 M	
N481	.132	.186	.403	4.60 M	
N6078	.134	.271	.507	5.48 M	
N5556-2	.153	.205	.040	4.37 M	
N5769	.155	.248	.317	4.80 M	

JP .	PART NO.	A HOLE	B O.D.	C LENGTH	PRICE PLUS SET-U
٨	N6063-1	.157	.380	.132	\$14.68 M
٨	N6063-2	.160	.444	.133	14.92 M
٨	N6064	.160	.615	.215	11.62 M
٨	N5451	.169	.242	.248	4.60 M
٨	N5332	.170	.255	.100	4.60 M
٨	N6324	.172	.375	.130	7.25 M
٨	N5765	.176	.282	.435	5.26 M
٨	N5770	.176	.302	.435	5.48 M
١	N6029	.180	.250	.244	9.96 M
٨	N5165-1	.183	.620	.560	27.40 M
١	N5218	.183	.272	.092	5.43 M
١	N5123	.184	.310	.475	5.92 M
١	N5771	.186	.316	.203	5.52 M
٨	N5767	.187	.282	.480	5.04 M
١	N6330	.187	.312	.305	4.76 M
١	N3-1-D142	3/16	5/16	5/16	22.90 M
٨	N3-1A	3/16	3/8	3/8	24.50 M
٨	N3-2	3/16	7/16	7/16	26.50 M
١	N5772	.185	.316	.173	5.46 M
١	N5289	.190	.308	.500	5.92 M
١	N235	.190	.316	.261	8.06 M
١	N233-1	.190	.316	.161	7.85 M
١	N233-2	.190	.318	.267	8.16 M
١	N278	.190	.435	.128	10.64 M

nylomatic division, morrisville, bucks county, pennsylvania

Issued 6-69

Issued 6-69

[†]Not included in Engineering Kit shown on Page four.





PLAIN BEARINGS, WASHERS, STAND-OFFS


- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- All fractional sizes are Black Nylon.

PART

- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.







C

В

PRICE


PART NO.	A HOLE	B O.D.	C LENGTH	PRICE PLUS SET-UP
N1097-1	.190	.750	.346	\$86.44 M
NFL-27	.192	.290	.133	9.74 M
N5137	.192	.465	.315	9.10 M
N2048	.192	.745	.372	54.10 M
N6341	.192	.375	.045	11.76 M
N5284	.192	.750	.070	9.40 M
N5442	.185	.910	.424	43.20 M
N5181	.193	.625	.246	11.60 M
N6016	.194	.314	.068	4.37 M
N2083	.194	.620	.378	51.02 M
N168	.194	.620	.984	64.40 M
N6232-1	.196	.441	.735	72.86 M
N5648	.195	.562	.334	13.80 M
N401	.198	.248	.510	5.28 M
NFL-7	.203	.622	.192	17.33 M
N6293	.203	.250	.140	9.94 M
N5321	.205	.468	.122	6.07 M
N6083	.207	.302	.130	4.60 M
N5957	.208	.377	.750	10.95 M
N5126	.209	.478	.126	14.90 M
N5085	.210	.500	.170	7.37 M
N6509	.220	.375	.304	5.53 M
N5625	.220	.625	.031	7.72 M
N5532	.224	.316	.204	4.82 M
N6835	.225	.375	.089	4.82 M
N5235	.225	.348	.114	4.82 M
N5773	.226	.316	.177	4.60 M
N5473	.228	.282	.300	4.66 M


1	NO.	HOLE	O.D.	LENGTH	PLUS SET-UP
	N6015	.230	.315	.069	\$4.37 M
	N5551-2	.249	.550	.252	14.63 M
	N6605	.250	.375	.203	7.40 M
	N4-1	1/4	3/8	3/8	23.80 M
-	N4-1A	1/4	7/16	7/16	26.10 M
	N4-2	1/4	1/2	1/2	28.20 M
	N5033-8	.252	.375	.456	9.40 M
	N5340	.252	.614	.247	13.50 M
	N5033-6	.253	.377	.250	11.16 M
Ì	N6349	.253	.372	1.589	15.54 M
	N5624	.254	.438	.378	8.40 M
	N6232-2	.254	.441	.315	68.57 M
	N5315	.254	.745	.715	61.14 M
	NFL-11	.255	.376	.354	21.13 M
	N5437	.255	.497	.251	8.00 M
	N5433-1	.255	.620	.097	11.08 M
	N306-1	.255	.630	.250	18.45 M
	N5712	.257	.493	.220	9.17 M
	N5171	.258	.632	.500	22.40 M
	N5990	.260	.378	.176	5.18 M
	N5551-1	.263	.565	.565	18.40 M
	N6164	.269	.500	.218	7.80 M
	N306	.272	.630	.250	18.45 M
	N5329	.273	.610	.250	10.50 M
	N5285	.285	.758	.126	14.63 M
	N2112	.294	.614	.932	49.67 M
	N5604	.308	.553	.485	15.05 M
- 3			THE RESERVE TO A STATE OF THE PARTY OF THE P	-	

nylomatic

PLAIN BEARINGS, WASHERS, STAND-OFFS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- · All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.





N5872-2 .308 .585 .132 15.36 M N8-1A 1/2 11/16 11/16 N5-1 5/16 7/16 7/16 24.30 M N8-2 1/2 3/4 3/4 N5-1A 5/16 1/2 1/2 27.10 M N5307 .503 .820 .095 N5-2 5/16 9/16 9/16 29.80 M N5307 .503 .820 .095 N6327 .312 .625 .220 10.36 M N5582-1 .504 .875 .125 N6326 .312 .625 .156 9.74 M N5640 .520 .750 .094 N5525-2 .314 .808 .427 58.52 M N9-1 9/16 11/16<	26.50 M 31.80 M 36.30 M 9.17 M 45.90 M 11.18 M 27.90 M 33.70 M 38.80 M 13.35 M 11.38 M 91.45 M
N5-1 5/16 7/16 7/16 24.30 M N8-2 1/2 3/4 3/4 N5-1A 5/16 1/2 1/2 27.10 M N5307 .503 .820 .095 N5-2 5/16 9/16 9/16 29.80 M N5582-1 .504 .875 .125 N6327 .312 .625 .220 10.36 M N5582-1 .504 .875 .125 N6326 .312 .625 .156 9.74 M N5640 .520 .750 .094 N6325 .312 .625 .094 9.53 M N9-1 9/16 11	36.30 M 9.17 M 45.90 M 11.18 M 27.90 M 33.70 M 38.80 M 13.35 M 11.38 M
N5-1A 5/16 1/2 1/2 27.10 M N5307 .503 .820 .095 N5-2 5/16 9/16 9/16 29.80 M N5582-1 .504 .875 .125 N6327 .312 .625 .220 10.36 M N5640 .520 .750 .094 N6326 .312 .625 .156 9.74 M N9-1 9/16 11/16	9.17 M 45.90 M 11.18 M 27.90 M 33.70 M 38.80 M 13.35 M 11.38 M
N5-2 5/16 9/16 9/16 29.80 M N5582-1 .504 .875 .125 N6327 .312 .625 .220 10.36 M N5640 .520 .750 .094 N6326 .312 .625 .156 9.74 M N9-1 9/16 11/16	45.90 M 11.18 M 27.90 M 33.70 M 38.80 M 13.35 M 11.38 M
N6327 .312 .625 .220 10.36 M N6326 .312 .625 .156 9.74 M N6325 .312 .625 .094 9.53 M N5525-2 .314 .808 .427 58.52 M N5525-1 .317 .750 .432 28.30 M N6836 .318 .442 .880 18.66 M N5852 .319 .433 .942 11.60 M N6122 .322 .528 .102 8.05 M N6-12 .3/8 1/2 1/2 24.60 M N6-1A 3/8 9/16 9/16 28.60 M N6-2 3/8 5/8 5/8 31.80 M N5065 .377 .554 .060 6.48 M	11.18 M 27.90 M 33.70 M 38.80 M 13.35 M 11.38 M
N6326 .312 .625 .156 9.74 M N6325 .312 .625 .094 9.53 M N5525-2 .314 .808 .427 58.52 M N5525-1 .317 .750 .432 28.30 M N6836 .318 .442 .880 18.66 M N5852 .319 .433 .942 11.60 M N6122 .322 .528 .102 8.05 M N2110 .348 .742 .992 62.47 M N6-1 3/8 1/2 1/2 24.60 M N6-1A 3/8 9/16 9/16 28.60 M N6-2 3/8 5/8 5/8 31.80 M N5065 .377 .554 .060 6.48 M	27.90 M 33.70 M 38.80 M 13.35 M 11.38 M
N6325 .312 .625 .094 9.53 M N5525-2 .314 .808 .427 58.52 M N5525-1 .317 .750 .432 28.30 M N6836 .318 .442 .880 18.66 M N5852 .319 .433 .942 11.60 M N6122 .322 .528 .102 8.05 M N2110 .348 .742 .992 62.47 M N6-1 3/8 1/2 1/2 24.60 M N6-1A 3/8 5/8 5/8 31.80 M N5065 .377 .554 .060 6.48 M	33.70 M 38.80 M 13.35 M 11.38 M
N5525-2 .314 .808 .427 58.52 M N5525-1 .317 .750 .432 28.30 M N6836 .318 .442 .880 18.66 M N5852 .319 .433 .942 11.60 M N6122 .322 .528 .102 8.05 M N2110 .348 .742 .992 62.47 M N6-1 3/8 1/2 1/2 24.60 M N6-1A 3/8 9/16 9/16 28.60 M N5065 .377 .554 .060 6.48 M	38.80 M 13.35 M 11.38 M
N5525-1 .317 .750 .432 28.30 M N6836 .318 .442 .880 18.66 M N5852 .319 .433 .942 11.60 M N6122 .322 .528 .102 8.05 M N2110 .348 .742 .992 62.47 M N6-1 3/8 1/2 1/2 24.60 M N6-1A 3/8 9/16 9/16 28.60 M N6-2 3/8 5/8 5/8 31.80 M N5065 .377 .554 .060 6.48 M	13.35 M 11.38 M
N6836 .318 .442 .880 18.66 M N5657 .565 .812 .094 N5852 .319 .433 .942 11.60 M N1097-3 .572 1.250 .220 N6122 .322 .528 .102 8.05 M N10-1 5/8 3/4 3/4 N2110 .348 .742 .992 62.47 M N10-1A 5/8 13/16 13/16 N6-1 3/8 1/2 1/2 24.60 M N10-2 5/8 7/8 7/8 N6-1A 3/8 9/16 9/16 28.60 M N5641 .630 1.000 .094 N6-2 3/8 5/8 5/8 31.80 M N5654 .675 .875 .094 N5065 .377 .554 .060 6.48 M N2115 .680 1.630 .125	11.38 M
N5852 .319 .433 .942 11.60 M N1097-3 .572 1.250 .220 N6122 .322 .528 .102 8.05 M N10-1 5/8 3/4 3/4 N2110 .348 .742 .992 62.47 M N10-1A 5/8 13/16 13/16 N6-1 3/8 1/2 1/2 24.60 M N10-2 5/8 7/8 7/8 N6-1A 3/8 9/16 9/16 28.60 M N5641 .630 1.000 .094 N6-2 3/8 5/8 5/8 31.80 M N5654 .675 .875 .094 N5065 .377 .554 .060 6.48 M N2115 .680 1.630 .125	2 424-115 1410
N6122 .322 .528 .102 8.05 M N2110 .348 .742 .992 62.47 M N6-1 3/8 1/2 1/2 24.60 M N6-1A 3/8 9/16 9/16 28.60 M N6-2 3/8 5/8 5/8 31.80 M N5065 .377 .554 .060 6.48 M	91.45 M
N2110 .348 .742 .992 62.47 M N10-1A 5/8 13/16 13/16 N6-1 3/8 1/2 1/2 24.60 M N10-2 5/8 7/8 7/8 N6-1A 3/8 9/16 9/16 28.60 M N5641 .630 1.000 .094 N6-2 3/8 5/8 5/8 31.80 M N5654 .675 .875 .094 N5065 .377 .554 .060 6.48 M N2115 .680 1.630 .125	
N6-1 3/8 1/2 1/2 24.60 M N10-2 5/8 7/8 7/8 N6-1A 3/8 9/16 9/16 28.60 M N5641 .630 1.000 .094 N6-2 3/8 5/8 5/8 31.80 M N5654 .675 .875 .094 N5065 .377 .554 .060 6.48 M N2115 .680 1.630 .125	33.60 M
N6-1A 3/8 9/16 9/16 28.60 M N5641 .630 1.000 .094 N6-2 3/8 5/8 5/8 31.80 M N5654 .675 .875 .094 N5065 .377 .554 .060 6.48 M N2115 .680 1.630 .125	42.60 M
N6-2 3/8 5/8 5/8 31.80 M N5654 .675 .875 .094 N5065 .377 .554 .060 6.48 M N2115 .680 1.630 .125	48.60 M
N5065 .377 .554 .060 6.48 M N2115 .680 1.630 .125	12.77 M
	11.60 M
	86.94 M
N5842 .378 .504 .375 12.17 M N11-1 11/16 13/16 13/16	35.50 M
N6044 .380 .506 1.002 19.32 M N11-1A 11/16 7/8 7/8	44.70 M
N189 .381 .525 .093 13.58 M N11-2 11/16 15/16 15/16	51.90 M
N5193 .390 .538 1.928 37.68 M N12-1 3/4 7/8 7/8	36.60 M
N6232-3 .495 .687 .234 69.33 M N12-1A 3/4 15/16 15/16	47.10 M
N7-1 7/16 9/16 9/16 26.00 M N12-2 3/4 1 1	55.40 M
N7-1A 7/16 5/8 5/8 30.10 M N2130 .759 1.000 .500	81.17 M
N7-2 7/16 11/16 11/16 33.90 M	
N6643 .500 .625 .168 19.80 M	F-11.5


nylomatic division, morrisville, bucks county, pennsylvania

Issued 6-69



PLAIN BEARINGS, WASHERS, STAND-OFFS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- · All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.



PART NO.	A HOLE	B O.D.	C LENGTH	PRICE PLUS SET-UP	PART NO.	A HOLE	B O.D.
N5655	.760	1.063	.094	\$14.50 M	N16-1	1	1 1/8
N5658	.790	1.000	.094	13.67 M	N16-1A	1	1 3/16
N13-1	13/16	15/16	15/16	38.60 M	N16-2	1	1 1/4
N13-1A	13/16	1	1	49.50 M	N5660	1.025	1.188
N13-2	13/16	1 1/16	1 1/16	58.90 M	*N17-1	1 1/16	1 3/16
N14-1	7/8	1	1	40.50 M	*N17-1A	1 1/16	1 1/4
N14-1A	7/8	1 1/16	1 1/16	52.30 M	*N17-2	1 1/16	1 5/16
N14-2	7/8	1 1/8	1 1/8	62.50 M	*N18-1	1 1/8	1 1/4
N5656	.890	1.125	.094	14.02 M	*N18-1A	1 1/8	1 5/16
N5659	.935	1.125	.094	14.02 M	*N18-2	1 1/8	1 3/8
N15-1	15/16	1 1/16	1 1/16	42.70 M	N6162	1.290	2.140
N15-1A	15/16	1 1/8	1 1/8	55.00 M	N5813	1.555	2.058
N15-2	15/16	1 3/16	1 3/16	66.20 M	N1106	1.612	3.170

^{*}Not included in Engineering Kit WSB-4 shown on Page four.


P.O.A. Price upon application.


nylomatic

FLANGED BEARINGS, INSULATORS, SLEEVES

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.







PART NO.	I. D. A	O. D. B	FL. DIA. F	FL. THK. T	O. L. L	PRICE PLUS SET-UP
NFL-19	.047	.070	.107	.017	.028	\$ 9.72 M
NFL-28	.064	.130	.188	.038	.094	9.74 M
N2079A	.094	.136	.212	.032	.090	24.24 M
N6847	.100	.154	.224	.028	.230	11.10 M
N422	.110	.134	.375	.024	.105	5.40 M
N5111	.116	.158	.316	.052	.148	4.60 M
N6505	.116	.158	.306	.047	.109	6.44 M
N5342	.118	.148	.312	.048	.085	4.60 M
N5212	.122	.150	.247	.046	.225	4.60 M
N5228	.124	.148	.253	.050	.148	4.60 M
N5722	.128	.187	.318	.028	.218	4.60 M
N267	.130	.163	:247	.250	.360	7.85 M
N2033	.132	.187	.275	.128	.330	8.05 M
N276	.132	.184	.308	.045	.112	7.62 M
NFL-6	.133	.370	.973	.038	.098	26.22 M
N471	.136	.234	.380	.096	.182	5.25 M
N5817	.138	.198	.250	.094	11/32	5.64 M
N5794	.143	.250	.325	.088	.676	7.18 M
N2079B	.145	.248	.372	.063	.125	24.66 M
N5464	.153	:222	.375	.050	.250	5.10 M
N5644	.155	.250	.312	.062	.688	6.77 M
N6039	.157	.250	.312	.010	.132	44.60 M
N5286	.158	.224	.375	.064	.252	4.86 M
N6310	.159	.250	.312	.062	.250	9.39 M
*NFL-20	.160	*.250	.383	.050	.440	16.00 M
N5316-1	.162	.192	.247	.144	.250	7.62 M
N5316-2	.162	.192	.247	.306	.408	7.85 M

^{*.062} radius on end of .250 shank dia.

Issued 6-69

nylomatic division, morrisville, bucks county, pennsylvania

PRICE

\$ 44.30 M

58.10 M

70.70 M

16.00 M

P.O.A.

P.O.A.

P.O.A.

P.O.A.

P.O.A.

P.O.A.

62.25 M

58.96 M

174.84 M

LENGTH PLUS SET-UP

C

1 1/8

1 1/4

1 3/16

.094

3/16

1/4

5/16

1 1/4

1 5/16

1 3/8

.098


.120


.254



FLANGED BEARINGS, INSULATORS, SLEEVES

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- · All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.






PART NO.	I. D.	O. D. B	FL. DIA. F	FL. THK. T	O. L. L	PRICE PLUS SET-UP
N6232-4	.164	.500	.625	.125	.281	\$70.59 M
N5408	.165	.255	.370	.053	.226	5.30 M
N5093	.172	.248	.308	.127	.208	4.83 M
N5043	.182	.270	.358	.052	.478	5.75 M
N5009	.185	.272	.364	.052	.570	5.96 M
NFL-21	.188	.230	.500	.035	.660	24.90 M
NF3-1	3/16	5/16	7/16	1/16	5/16	25.42 M
NF3-1A	3/16	3/8	1/2	1/16	3/8	27.85 M
NF3-2	3/16	7/16	9/16	1/16	7/16	30.71 M
N260	.192	.308	.438	.180	.255	11.52 M
N5040	.193	.375	.550	.093	.186	7.78 M
N5966	.195	.236	.340	.042	.225	4.90 M
N5919	.195	.282	.500	.032	.065	7.65 M
N6021	.197	.270	.360	.025	.128	4.75 M
N6653	.200	.502	.625	.109	.375	18.10 M
N6295	.203	.250	.375	.062	.222	9.53 M
NFL-16	.204	.340	.684	.030	.187	11.00 M
NFL-14	.208	.315	.616	.055	.102	11.50 M
NFL-15	.216	.367	.553	.105	.160	11.50 M
N288	.222	.317	.500	.328	.630	19.56 M
N5182	.238	.356	.658	.106	.278	9.36 M
ND71	1/4	3/8	1/2	1/16	3/8	26.70 M
NF4-1A	1/4	7/16	9/16	1/16	7/16	30.00 M
NF4-2	1/4	1/2	5/8	1/16	1/2	33.00 M
N5859	.252	.386	.502	.065	.435	8.20 M
N5389	.252	.310	.500	.064	.255	5.40 M
N5369	.252	.500	.870	.375	.996	42.75 M
N5788	.245	.283	.667	.100	.232	9.17 M
N6294	.253	.372	.750	.062	.288	27.63 M


nylomatic

FLANGED BEARINGS, INSULATORS, SLEEVES

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.








PART NO.	I. D. A	O. D.	FL. DIA.	FL. THK.	O. L. L	PRICE PLUS SET-UP
110.				·	-	1 200 021-01
N5209	.265	.305	.440	.032	.390	\$ 6.47 M
N2052	.257	.442	.688	.078	.437	48.35 M
N458	.257	.312	.569	.068	.128	6.05 M
N5330-1	.257	.378	.622	.064	.279	9.15 M
N5433-2	.258	.375	.620	.134	.888	18.90 M
N5550-1	.258	.439	.620	.188	.500	29.72 M
N5187	.260	.312	.625	.032	.198	8.05 M
N5330-2	.260	.375	.625	.062	.218	8.73 M
N5041	.261	.488	.622	.125	.250	12.84 M
N5214	.257	.336	.500	.049	.368	8.28 M
N5067-4	.263	.309	.438	.030	.286	14.68 M
N5142-2	.265	.510	1.000	.167	.634	56.75 M
N5154	.292	.438	.617	.035	.564	10.72 M
N6323	.312	.373	.500	.093	.250	13.52 M
ND117	5/16	7/16	9/16	1/16	7/16	27.57 M
NF5-1A	5/16	1/2	5/8	1/16	1/2	31.42 M
NF5-2	5/16	9/16	11/16	1/16	9/16	35.48 M
N443	.314	.350	.508	.056	.202	6.70 M
N5067-8	.318	.363	.496	.028	.280	8.05 M
N6076	.318	.375	.502	.180	.334	7.36 M
N6375	.318	.440	.622	.035	.564	15.00 M
N5934	.322	.493	.744	.128	.650	16.60 M
N426	.322	.455	.704	.058	.145	8.28 M
N5145-3	.325	.570	.660	.063	.295	10.74 M
N5412-1	.327	.502	.760	.082	.460	14.38 M
N427	.335	.450	.620	.046	.228	8.73 M
ND104	3/8	1/2	5/8	1/16	1/2	28.00 M
NF6-1A	3/8	9/16	11/16	1/16	9/16	33.57 M
NF6-2	3/8	5/8	3/4	1/16	5/8	38.14 M






FLANGED BEARINGS, INSULATORS, SLEEVES

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.






PART NO.	I. D. A	O. D. B	FL. DIA. F	FL. THK. T	O. L. L	PRICE PLUS SET-UP
N5007-1	.378	.494	.745	.220	.438	\$15.70 M
N5007-2	.378	.494	.745	.130	.350	13.73 M
N5007-3	.380	.496	.750	.045	.257	11.52 M
N5901	.380	.626	.742	.262	.388	18.36 M
N5412-2	.382	.502	.760	.082	.460	13.50 M
N5036	.382	.496	.817	.061	.295	12.60 M
N5965	.384	.632	.755	.248	1.130	33.12 M
N5403	.385	.560	1.500	.056	.307	32.40 M
NFL-13	.388	.508	.630	.070	.376	11.94 M
N5145-2	.388	.570	.660	.063	.295	10.08 M
NF7-1-D182	7/16	9/16	11/16	1/16	9/16	29.85 M
NF7-1A	7/16	5/8	3/4	1/16	5/8	35.85 M
NF7-2	7/16	11/16	13/16	1/16	11/16	41.14 M
N5145-1	.450	.570	.660	.063	.345	9.87 M
N6048	.465	.627	.880	.037	.255	12.63 M
N5568	.500	.735	1.120	.100	.370	26.96 M
NF8-1-D145	1/2	5/8	3/4	1/16	.5/8	30.71 M
NF8-1A	1/2	11/16	13/16	1/16	11/16	38.66 M
NF8-2	1/2	3/4	7/8	1/16	3/4	44.50 M
N2131	.503	.580	.818	.040	.296	69.08 M
N5136	.504	.689	.810	.125	.444	16.15 M
N6147	.512	.636	3/4	1/16	.260	12.63 M
NF9-1	9/16	11/16	7/8	1/16	11/16	32.73 M
NF9-1A	9/16	3/4	15/16	1/16	3/4	40.82 M
NF9-2	9/16	13/16	1	1/16	13/16	48.28 M
NFL2-2	.570	.658	.812	.050	.362	47.25 M
N2129	.613	1.000	1.125	.097	.465	94.47 M
N6077	.616	.816	1.250	.098	.497	37.68 M
NF10-1-D153	5/8	3/4	15/16	1/16	3/4	34.10 M


nylomatic

FLANGED BEARINGS, INSULATORS, SLEEVES

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, natural color.
- All fractional sizes are Black Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.







PART NO.	I. D. A	O. D. B	FL. DIA. F	FL. THK. T	O. L. L	PRICE PLUS SET-UP
NF10-1A	5/8	13/16		1/16	13/16	\$47.00 M
NF10-2	5/8	7/8	1 1/16	1/16	7/8	55.50 M
NF11-1	11/16	13/16	1	1/16	13/16	37.00 M
NF11-1A	11/16	7/8	1 1/16	1/16	7/8	50.00 M
NF11-2	11/16	15/16	1 1/8	1/16	15/16	60.30 M
NF12-1-D141	3/4	7/8	1 1/16	1/16	7/8	38.50 M
NF12-1A	3/4	15/16	1 1/8	1/16	15/16	53.40 M
NF12-2	3/4	1	1 3/16	1/16	1	65.40 M
N2136	.757	1.000	1.495	.111	.593	87.93 M
NFL2-1	.758	.850	.995	.050	.175	46.37 M
NF13-1	13/16	15/16	1 1/8	1/16	15/16	41.10 M
NF13-1A	13/16	1	1 3/16	1/16	1	56.80 M
NF13-2	13/16	1 1/16	1 1/4	1/16	1 1/16	70.20 M
N6384	.875	1.250	1.438	.125	1.500	157.62 M
NF14-1	7/8	1	1 3/16	1/16	1	44.14 M
NF14-1A	7/8	1 1/16	1 1/4	1/16	1 1/16	60.80 M
NF14-2	7/8	1 1/8	1 5/16	1/16	1 1/8	75.40 M
NF15-1	15/16	1 1/16	1 1/4	1/16	1 1/16	47.61 M
NF15-1A	15/16	1 1/8	1 5/16	1/16	1 1/8	64.70 M
NF15-2	15/16	1 3/16	1 3/8	1/16	1 3/16	80.76 M
NF16-1	1	1 1/8	1 5/16	1/16	1 1/8	49.57 M
NF16-1A	1	1 3/16	1 3/8	1/16	1 3/16	69.10 M
NF16-2	1	1 1/4	17/16	1/16	1 1/4	87.85 M
NF17-/I	1 1/16	1 3/16	1 3/8	1/16	1 3/16	P.O.A.
NF17-1A	1 1/16	1 1/4	17/16	1/16	1 1/4	P.O.A.
NF17-2	1 1/16	1 5/16	1 1/2	1/16	1 5/16	P.O.A.
NF18-1	1 1/8	1 1/4	17/16	1/16	1 1/4	P.O.A.
NF18-1A	1 1/8	1 5/16	1 1/2	1/16	1 5/16	P.O.A.
NF18-2	1 1/8	1 3/8	1 9/16	1/16	1 3/8	P.O.A.

P.O.A. Price upon application.



nylomatic ROLLERS-SOLID AND CORED

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 20M pieces.
- Prices subject to change without notice.

	$D \rightarrow$	→ D →		r → D →	← D →
<u>↓</u> 1			1 30		
c A	4		1 55 €	H	 -
Type A	Type B	Type C	Type D	Type E	B Type F


PART NO.	TYPE	O. D. A	В	I. D. C	O. L. D	PRICE PLUS SET-UP
N5648	A	.562	.334	.195		\$ 13.80 M
N5165-1	A	.620	.560	.183	_	27.40 M
N2083	A	.620	.378	.194		51.02 M
N168	A	.620	.984	.194		64.40 M
N1097-1	Α	.750	.346	.190		86.44 M
N2048	Α	.745	.372	.192	-	54.10 M
N5442	A	.910	.424	.185	_	43.20 M
N5181	A	.625	.246	.193	_	11.60 M
N5340	Α	.614	.247	.252		13.50 M
N5315	A	.745	.715	.254	_	61.14 M
N306-1	Α	.630	.250	.255		18.45 M
N5171	Α	.632	.500	.258	_	22.40 M
N5525-2	Α	.808	.427	.314	:-	58.52 M
N2110	Α	.742	.992	.348	_	62.47 M
N1097-3	Α	1.250	.220	.572	() <u></u> -1	91.45 M
N5151	В	.188	.112	.100	.128	4.37 M
NFL-25	В	.372	.158	.196	.177	9.95 M
N1125-1	В	.875	.308	.187	.338	37.80 M
N1097-2	С	1.073	.206	.254	.218	75.80 M
N1097-4	С	1.183	.212	.315	.228	87.40 M
N1125-2	С	1.187	.200	.343	.218	49.00 M
N1097-5	С	1.250	.212	.254	.225	93.62 M
N5005	D	1.063	1.000	.256	0-0	80.57 M
N5758	D	1.125	1.422	.406		93.84 M
N5347	D	1.437	.625	.190	_	63.90 M
N6654	D	1.475	.674	.252		96.10 M
N6604	D	1.610	.437	.251		107.80 M
N1185	D	2.445	.625	.503		239.40 M
NS1200	D	2.875	.625	.500	1-1	255.00 M
N6603	E	1.824	.340	.443	.410	67.35 M
N6382	E	1.918	.937	.302	.981	221.06 M
N6242	E	2.000	.500	.502	.540	135.52 M
N2016	F	1.330	.285	.248	.655	69.55 M


nylomatic division, morrisville, bucks county, pennsylvania

nylomatic WHEELS AND ROLLERS



- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.






Type "X"

Type "Y"

PART NO.	TYPE	O. D. A	THICK B	BORE C	CT. BORE D	PRICE PLUS SET-UI
N5174	. X	.500	.300	.195	.255	\$ 9.12 M
N5175	X	.620	.300	.198	.258	14.60 M
N5203A	Y	.748	.238	.255	\ <u>-</u>	49.90 M
N6281	X	.750	.156	.258	20	18.06 M

2-PIECE ROLLER



	Diam. A	В	С	D	E	F	PRICE
N1069	1.125	.940	.312	.515	.262	.472	\$50.64 M + SET-UF
N1070	.758	.625	.255	.316	.170	.360	\$21.60 M + SET-UP

nylomatic division, morrisville, bucks county, pennsylvania





30

nylomatic

WITH COUNTERBORED HOLES


- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.






		1
		A
-	TYPE "C"	Į.

PART NO.	A (DIA.) HOLE	C-BORE B (DIA.)	C O.D.	D-DEPTH C-BORE	T LENGTH	PRICE PLUS SET-UP
N6238	.158	.344	.437	.052	.187	\$ 9.08 M
N424	.194	.318	.440	.073	.255	7.80 M
(*C)N5312	.195	.430	.750	.213	.348	21.32 M
(*C)N5273	.195	.412	.750	.065	.200	11.82 M
(*C)N5675	.208	.500	.862	.148	.496	40.12 M
N5116	.250	.463	.885	.265	.314	23.30 M
(*C)N6229	.255	.375	.875	.187	.375	23.80 M
(*C)N2092	.435	1.114	1.492	.137	.632	138.18 M






PART NO.	TYPE	A (DIA.) HOLE	B (DIA.) CT'BORE	C O.D.	D DEPTH CT'BORE	F (DIA.) FLANGE		L LENGTH	PRICE PLUS SET-UP
N6094	Х	.187	.275	.383	.062	.502	.022	.125	\$ 6.48 M
N6045	Х	.200	.395	.280	.015	.670	.065	.196	11.08 M
N2006	X	.238	.302	.340	.270	.432	.057	.486	10.85 M
N5645	Х	.250	.375	.375	.078	.750	.188	.344	15.48 M
N112	Х	.314	.500	.440	.063	.687	.259	.406	49.45 M
N5375	Х	.320	.503	.562	.063	.750	.100	.438	15.05 M
N1049	Y	.360	.875	.625	.062	1.215	.214	.410	38.70 M

nylomatic division, morrisville, bucks county, pennsylvania

nylomatic

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.









TYPE B

TYPE C





PART NO.	TYPE	FL. DIA. W	FL. THK. X	HOLE SIZE Y	O. A. L. Z	PRICE PLUS SET-UP
N5853	A	.502	.065	.257	.406	\$18.00 M
N5141	A	.695	.032	.255	.751	20.58 M
N5806	A	.887	.046	.580	.759	78.40 M
N6261	A	1.000	.048	.633	1.000	61.78 M
N6262	A	1.125	.048	.774	1.125	61.10 M
N6340	A	1.375	.030	.593	.600	92.56 M
N1065	A	1.384	.067	.657	1.187	109.50 M
N418	В	.422 × .496	.030	.090 × .202	.555	45.48 M
N5323	С	.748	.040	.192	.697	31.08 M
N467	D	see diagram				28.43 M
N6153	E	see diagram				59.62 M

nylomatic division, morrisville, bucks county, pennsylvania

Issued 6-69



nylomatic RIVETS, BUTTONS, PLUGS

- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.

Round Head	Brazier Head	Flat Head	Fillister Head
Type "A"	Type "B"	Type "C"	Type "D"
Z	$\begin{array}{c c} & & & z \\ \hline & & & \\ \hline \end{array}$	X X X	Z X W

PART NO.	HEAD TYPE	SHANK DIA. W	SHANK LEN. X	HEAD DIA. Y	HEAD THK.	PRICE PLUS SET-UP
N5027	Α	.062	.106	.092	.050	\$ 4.30 M
N2002	A	.090	.050	.156	.065	4.30 M
N277	Â	.093	.160	.190	.060	5.20 M
N385	Â	.108	.045	.200	.092	5.20 M
N5352	A	.126	.065	.216	.110	4.58 M
N6108	Ä	.181	.470	.250	.093	6.68 M
N6112	В	.148	.300	.405	.100	4.80 M
N497-1R	В	.150	.312	.380	.078	5.04 M
N498-R	В	.158	.188	.535	.090	5.25 M
N497-2R	В	.160	.075	.385	.075	4.80 M
N428-1R	В	.160	.250	.381	.100	5.04 M
N5328	C	.075	.100	.200	.020	4.30 M
N2100	C	.089	.038	.192	.268	5.42 M
N5609-1R		.091	.060	.155	.065	4.30 M
N5609-2R	Č	.091	.060	.155	.096	4.32 M
N5609-3R	Č	.091	.060	.155	.128	4.37 M
NFL-8	00000	.092	.033	.156	.032	4.37 M
N2093	C	.092	.038	.184	.080	5.12 M
N416-R	C	.116	.405	.192	.068	4.80 M
N5326-R	C	.120	.152	.187	.028	6.03 M
N5391	C	.125	.190	.403	.082	6.08 M
N5344-1R	C	.126	.245	.340	.128	14.70 M
N5462-R	C	.134	.285	.250	.090	4.82 M
N421-3	C	.158	.185	.314	.035	4.80 M
N5011-R	C	.158	.178	.345	.082	5.02 M
N428-2R	C	.160	.245	.386	.110	5.28 M
N6080	00000000	.176	.250	.464	.100	9.84 M
N5165-2	С	.186	.495	.618	.190	21.90 M
N2053-R	С	.192	.220	.355	.068	10.20 M
N2117-R	С	.203	.214	.252	.098	10.42 M
N5407	D	.068	.046	.125	.082	4.30 M
N478	D	.069	.050	.127	.110	4.30 M
N5246	D	.076	.062	.156	.093	4.30 M
N5341	D	.089	.041	.125	.156	5.94 M
N5188	D	.093	.060	.155	.055	4.30 M
N421	D	.158	.185	.308	.058	4.80 M
N421-1R	D	.158	.195	.310	.095	4.80 M


The letter "R" following part number designates a chamfer on end of shank.

nylomatic division, morrisville, bucks county, pennsylvania

nylomatic **PULLEYS**



- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 25M pieces.
- Prices subject to change without notice.



Type A

Type B

Type C Type D

Type E Type F

PART NO.	TYPE	O. D. V	SLOT O. D.	WIDTH X	SLOT WTH.	BORE Z	PRICE PLUS SET-UP
N5269	A*	.304	.165	.125	.030	.085	\$ 9.56 M
N5215	A*	.398	.308	.123	.043	.073	14.68 M
N6172	В	.314	.252	.090	.032	.070	17.25 M
N5587	В	.878	.654	.404	.125	.194	36.16 M
N6639	С	.500	.375	.125	, - .	.129	15.40 M
N5359	D	.500	.400	.308	=	.128	16.68 M
N6507	D	.500	.405	.157	.093	.095	21.84 M
N6227-1	D	.625	.437	.250	.187	.257	41.32 M
N6227-2	D	.875	.687	.250	.187	.257	45.36 M
N1061	D	.977	.625	.408	.343	.252	47.88 M
N6227-3	D	1.000	.812	.250	.187	.257	63.88 M
N1060	D	1.018	.848	.380	.268	.332	47.45 M
N6091	D	1.110	.875	.316	.190	.192	80.30 M
N6222	D	1.125	.812	.397	.218	.638	52.42 M
N5747	D	1.255	.994	.623	.390	.508	69.58 M
N6173-7171	D	1.372	1.000	.344	.275	.254	51.06 M
**N1057	D	1.400	.988	1.000	.875	.494	128.95 M
N1033	D	2.615	2.120	.495	.250	.506	222.60 M
N402	Е	.680	.520	.310		.125	22.34 M
N5147	F	.586	.345	.222	.063	.132	16.48 M
N2064	G	.775	.630	.120	.063	.382—.530	45.94 M
N7092	С	5/8	.475	.185	_	.258	19.90 M


A* Pulley without hub either side.

^{**}Has hub 5/8 O.D. x .105 Projection one side.



SHOULDER WASHERS

- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon, Delrin & Teflon.
- Prices upon application.



SCREW SIZE	O. D.	SHOULDER DIA.	I. D.	
#2	1/4	.154	.090	
4	1/4	.186	.116	
6	5/16	.186	.142	
8	3/8	.246	.168	
10	3/8	.312	.194	
12	3/8	.312	.220	
1/4	1/2	.312	.254	
5/16	1/2	.370	.317	
3/8	5/8	.437	.380	
7/16	3/4	.527	.443	
1/2	3/4	.590	.505	

SHOULDER THICKNESS	$.030 \pm$.010
FLANGE THICKNESS	.050 ±	.010

Prices and Delivery Dates on Request.

nylomatic STAMPED WASHERS

- No set-up charge.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Prices upon application.



Listed below are the sizes of stamped washers we can furnish without tooling charges.

These are available in nylon, De!rin*, Nylatron GS**, polyethylene and Teflon*.

Standard thicknesses are .032", .047", .062", .093" and .125".

Standard tolerances on O.D. x I.D. \pm .004, thickness \pm 5 to 10%.

Prices upon application.

Any punching is based on the wall thickness (distance from I. D. to O. D.) being at least as great as the stock thickness.

I. D.	O. D.	I. D.	O. D.	I. D.	O. D.
1/8	3/16	7/16	3/4	7/8	1 1/4
1/8	1/4	7/16	7/8	7/8	1 1/2
1/8	3/8	7/16	1	31/32	1 1/8
1/8	1/2	1/2	5/8	15/16	1 1/4
5/32	1/4	1/2	3/4	1	1 1/4
3/16	1/4	1/2	7/8	1	1 1/2
3/16	3/8	33/64	7	1	1 5/8
3/16	1/2	9/16	11/16	1	1 3/4
13/64	9/16	9/16	3/4		1 15/16
1/4	3/8	9/16	7/8	1 1/8	1 1/2
1/4	1/2	9/16	1	1 1/8	1 5/8
1/4	9/16	5/8	3/4	1 1/8	1 3/4
1/4	5/8	5/8	7/8	1 1/8	1 15/16
1/4	3/4	5/8	1	1 1/4	1 1/2
5/16	1/2	41/64	1 1/8	1 1/4	1 5/8
5/16	9/16	11/16	3/4	1 1/4	1 3/4
5/16	5/8	11/16	7/8	1 1/4	1 15/16
5/16	3/4	11/16	1	1 3/8	1 5/8
3/8	1/2	11/16	1 1/8	1 3/8	1 3/4
3/8	9/16	3/4	1	1 3/8	1 15/16
3/8	5/8	3/4	1 1/8	1 1/2	1 3/4
3/8	3/4	3/4	1 1/4	1 1/2	1 15/16
3/8	1	3/4	1 1/2	1 11/16	2 3/4
7/16	5/8	7/8	1 1/8	2 3/8	3 1/2


(*Reg. trade name—DuPont Co. **Reg. trade name—Polymer Corp.)

nylomatic division, morrisville, bucks county, pennsylvania




nylomatic MISCELLANEOUS PARTS


- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.




PAD N6138 \$11.52 M + SETUP




WIRE CLAMP N5590 \$5.85 M + SETUP






BEVEL WASHER
N6104 \$12.70 M + SETUP




SPLIT BEARING
N5883 \$114.40 M + SETUP




PUSH BUTTON

N6136 \$43.85 M + SETUP


BEARING
NFX-3 \$16.00 M + SETUP



SCREW N6287 \$15.68 M + SETUP



HOLDER
NFX-1 \$9.75 M + SETUP



SPLIT CABLE EYE

Part No.	Diam.	В	С	Price per Pair
N5754	.250	.780	1.060	\$64.44 M + Setup
N5755	.500	.490	.815	\$56.58 M + Setup

CABLE EYE


N6005 \$85.56 M + SETUP

Issued 6-69


mylomatic MISCELLANEOUS PARTS




- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.




ROLLER N5759 \$31.74 M + SETUP




WHEEL N5954 \$32.72 M + SETUP




N5843 \$4.88 M + SETUP




ANGLE SLIDE
N5255 \$11.60 M + SETUP




GLIDE N5254 \$41.00 M + SETUP




SLIDE N5600-1 \$13.98 M + SETUP




INSERT
N5952 \$4.60 M + SETUP




SPLIT RIVET
N5518 \$5.04 M + SET-UP




BUTTON N5635 \$5.43 M + SETUP



SPLIT BUTTON
N6103 \$5.32 M + SETUP



THUMB SCREW
N5939 \$105.00 M + SETUP




SLIDE CUP N6002 \$9.78 M + SETUP




mylomatic MISCELLANEOUS PARTS


- A \$25.00 set-up charge applies to each part ordered.
- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.




BUTTON N6112 \$5.07 M + SET-UP




ROLLER N6238 \$9.08 M + SET-UP




N6437 \$84.00 M + SET-UP







BRIDGE N170 \$22.89 M + SET-UP




RETAINING RING N1127 \$181.28 M + SET-UP




ADJUSTING NUT N5951 \$63.70 M + SET-UP



HINGE BLOCK N5992 \$141.45 M + SET-UP




N6189 \$10.00 M + SET-UP




GUIDE N6064 \$11.62 M + SET-UP

Issued 6-69



BUTTON
NFL30 \$17.20 M + SET-UP




mylomatic MISCELLANEOUS PARTS



- Refer to page 3 for General Specifications.
- Standard material is Dupont #101 Nylon.
- Apply for prices on quantities larger than 50M pieces.
- Prices subject to change without notice.

NYLON FLOOR SAVERS FOR ALL WOOD FURNITURE









*Supplied with shoulder nail.

Drive shoulder nail into center of leg with hammer until collar touches wood. Lightly tap FLOOR SAVER onto exposed pin.


Made of durable, resilient Nylon to protect all types of floors.




BUSHING N5063 \$5.52 M + SET-UP




BEARING N271 \$8.52 M + SET-UP




GROMMET N2025 \$20.10 M + SET-UP





BUSHING N6216 \$15.47 M + SET-UP



GUIDE BUSHING N6028 \$6.86 M + SET-UP

ANNOUS AN

nylomatic

PHYSICAL PROPERTY CHART

		Test					TFE-
Property	Units	Method ASTM	NYLON 101	DELRIN	Glass Filled DELRIN	DELRIN A. F.	Fluoro- carbon
Tensile Strength, 73°F. Elongation, 73°F. Modulus of Elasticity, 73°F. Flexural Strength, 73°F. Hardness, Rockwell, 73°F. Durometer, 73°F. Tensile Impact	psi % psi psi ft. lbs./sq. in.	D-638 D-638 D-638 D-790 D-785 D-676	9,000-12,000 20-200 250,000-400,000 12,500-14,000 R110-120 D80-85 90-180	10,000-12,000 20-75 360,000-500,000 14,100-15,500 R120-R122 — 40-80	8500 7 880,000 11,000 R118 —	6900 12 400,000 R118 — —	1,500-5,000 75-350 50,000-90,000 No Break R10-20 D55-70 30-200
Coef. of Linear Thermal Exp. Deformation Under Load 122°F., 2,000 psi Heat Distortion, 264 psi Temperature, 66 psi Melting Point	in./in./°F. % °F. °F.	D-696 D-621 D-648 D-789	5.5 x 10 1.0-3.0 200-450 400-460 496±9	4.5 x 10 0.4-0.5 212 338 347	2.0-4.5 x 10 .5 315 345 . 347	4.5 x 10 — 212 329 370-410	5.5 x 10 3-7 120 270 621±9
Dielectric Strength Short Time (.080" Thickness) Volume Resistivity Dielectric Canstant, 60 cy. 10 ³ cy. 10 ⁶ cy. 10 ⁸ cy. Dielectric Loss Tangent, 60 cy. 10 ³ cy. 10 ⁶ cy.	volts/mil OHM-CM	D-149 D-257 D-150 D-150	300-400 4.5 × 10 3 4.1 4.0 3.4 0.014 0.02 0.04	500 6 × 10 4			10 2.0-2.1 2.0-2.1 2.0-2.1 2.0-2.1 <0.0005 <0.0005 <0.0005 <0.0005
Resistant To: Not Resistant To:			Common solvents, hydro- carbons, esters, ketones, alka- lis, dilute acids. Phenol, formic acid, concen- trated mineral acids.	Practically all solvents, hydrocarbons, esters, ketones, some dilute acids and some dilute alkalis. Most acids and bases.	Practically all solvents, hydrocarbons, esters, ketones, some dilute acids and some dilute alkalis. Most acids and bases.	Practically all solvents, hydrocarbons, esters, ketones, some dilute acids and some dilute alkalis. Most acids and bases.	All chemicals and solvents, except molten alkali metals and flourine. Halogenated solvents absorbed to minor degree at elevated temperatures and pressures.
Water Absorption Immersion (24 hrs.) Saturation (Boiled to Constant Wt.) Equilibrium (50% R.H. 73°F.) Specific Gravity Coefficient of Friction (No Lubricant) Mil. Specs.	% % 	D-570	0.6-1.5 7-9 2.5 1.14-1.15 .13 milp— 17091B milm—	0.12-0.25 0.2 1.420-1.435 .13	.25 .20 1.56 .2	.06 — 1.54 .0515	0.00-0.05 2.1-2.3 .04 AMS— 3651B
	Durometer, 73°F. Tensile Impact Coef. of Linear Thermal Exp. Deformation Under Load 122°F., 2,000 psi Heat Distortion, 264 psi Temperature, 66 psi Melting Point Dielectric Strength Short Time (.080" Thickness) Volume Resistivity Dielectric Canstant, 60 cy. 10³ cy. 106 cy. 108 cy. Dielectric Loss Tangent, 60 cy. 10³ cy. 106 cy. 108 cy. Resistant To: Water Absorption Immersion (24 hrs.) Saturation (Boiled to Constant Wt.) Equilibrium (50% R.H. 73°F.) Specific Gravity Coefficient of Friction (No Lubricant)	Durometer, 73°F. Tensile Impact Coef. of Linear Thermal Exp. Deformation Under Load 122°F., 2,000 psi Heat Distortion, 264 psi Temperature, 66 psi Melting Point Dielectric Strength Short Time (.080" Thickness) Volume Resistivity Dielectric Canstant, 60 cy. 10³ cy. 106 cy. 108 cy. Dielectric Loss Tangent, 60 cy. 108 cy. Dielectric Loss Tangent, 60 cy. 108 cy. Resistant To: Water Absorption Immersion (24 hrs.) Saturation (Boiled to Constant Wt.) Equilibrium (50% R.H. 73°F.) Specific Gravity Coefficient of Friction (No Lubricant)	Tensile Impact Tensile Inpact Tensile Impact Tensile Inpact Tensile Inpact	Durometer, 73°F. Tensile Impact Ft, Ibs./sq. in. D-676 D80-85 90-180	Durometer, 73°F. Tensile Impact Te	Durometer, 73° F. Tensile Impact ft. lbs./sq. in. D-676 D80-85	Durometer, 73 ° F. Fransile Impact Transile Impact Transil

